
т	۵	н <b>т</b>	m	0







LAYOUT SHOWN AS

Keying Shown as example

Connector dimension

Nominal

Dim

## CHARACTERISTICS

ω

-Standard : Based on MIL-DTL-38999 Series III

$\sim$	Standard . Dasca on h	The Dife 30333 Series III									
$\sim$	-Shell Material	: Composite				Р	3.25±0.2				
						РР	4.93±0.2				
	-Shell Plating	: Nickel				R1	20.62				
	-Insulator	: Thermoplastic				R2	18.26				
	-Contacts	: Copper Alloy				S	26.2±0.3				
	-Seals & Grommet	: Silicon Elastomer				V' W'	19.5+1.4/-0 2.1/3.65				
$\sim$	-Contact Plating	: Gold over copper Alloy 0.8	8µm minimum			Z'	32 Max				
	-Durability	: 500 Mating cycles				VV THREAD	M15x1-6g		Γ		
	-Delivered without Sou										
	-Temperature Range	<ul> <li>-65°C to +200°C</li> </ul>									
		•							A	07-10-20	)16
	-Salt Spray	: 2000 hours									
	-Mass	: 10.6 g ± 10%							ISS	DATE	
									Designe	ed By:	
										TITLE	
	BASIC SERIES:	8D 0	- 11 M	22	S N	L			SCA	ALE	
	DASIC SERIES.	0	- 11 11	22							-[-
<b></b>	SHELL TYPE : Square	-lange Receptacle					Delivered W/	O Contacts	N	A	
	CONTACT TYPE : Sta	ndard Crimp Contact					ORIEN	TATION : N	60		
	SHELL SIZE : 11					CONTACT TYPE : SOCKET(500 Matings)				SOURIAU	
					I				FORM	AAT	
	PLATING : M =	Nickel					CONTACT LAYO	OUT : 11-22			
								_	A	3	
·	Н	G			F		E	1	D		

SOURIAU shall not be liable for due to a use of the Products the Specifications issued by either

(professional recommend Cour



С

	Φ		⊳			
				4		
OUT SHOWN AS	EXAMPLE			3		
hot be liable for any non-conformity or damage of the Products which does not comply with issued by either of the Parties or by a third party onal recommendation, technical notice.) $\label{eq:country_jurisdiction & Control List} \\\hline FR & Not Listed \\ \hline N: 8D011M22SNL \\ \hline$						
n - by		CUSTOMER	MOD N	0		
CUSTOMER DRAWING Composite Receptacle 8D series						
General linear NPRDS / PROJECT Tolerances: 859 ±						
.SOURIAU.COM it must not be reproduced or communicated without permission						
SOURIAU DRG N°         SHEET           8D011M22SNL-C         1/2						
	В		Α			

4	(	Contact Layout 22*				SQUARE FLANGE RECEPTAC REAR MOUNTIN	Panel Cu
	Ctc A	4#22D 11-22 X Y 1.905 1.905					ØA
သ	B C D	1.905     -1.905       -1.905     -1.905       -1.905     1.905					Dim ØA ØAA R1 ØT
						due to a u the Specificati	all not be liable for use of the Products ons issued by either essional recommend
2							Cou F PN: 8D011
						-10-2016 First Release DATE Latest modific /: Da	
1					TIT SCALE NA		General linear Tolerances: ±
					FORMAT A3		N.SOURIAU SOURIA 8D011N
	Н	G	F	E \	D	C	

Т

ш

т

G

0

