



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Aluminium
- Shell Plating : Black Zinc Nickel
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered with Souriau contacts and Accessories
- Temperature Range : -65°C to +175°C
- Salt Spray : 500 hours
- Mass : 29.43 g ± 10%


| Connector dimension |               |
|---------------------|---------------|
| Dim                 | Nominal       |
| P                   | 3.25±0.2      |
| PP                  | 4.39±0.2      |
| R1                  | 24.61         |
| R2                  | 23.01         |
| S                   | 31±0.3        |
| V                   | 20.83+0/-1.25 |
| W                   | 2.1/2.5       |
| Z                   | 31.5 Max      |
| VV THREAD           | M22x1-6g      |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

**PN: 8D015Z18SE**

|                |                                       |                                |                                                                                                       |
|----------------|---------------------------------------|--------------------------------|-------------------------------------------------------------------------------------------------------|
| A              | 18-10-2016                            | First Release                  |                                                                                                       |
| ISS            | DATE                                  | Latest modification - by       | MOD N°                                                                                                |
| Designed By:   |                                       | Date:                          | <b>CUSTOMER DRAWING</b>                                                                               |
| <b>TITLE</b>   | <b>Aluminium Receptacle 8D series</b> |                                |                                                                                                       |
| SCALE          | NA                                    | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b>                                                                         |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                |                                | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D015Z18SE-C</b>    |                                | SHEET<br>1/2                                                                                          |



Contact Layout



| Contacts<br>(Insert arrangement 15-18) |             |             |                     |             |             |
|----------------------------------------|-------------|-------------|---------------------|-------------|-------------|
| Contact position ID                    | Location    |             | Contact position ID | Location    |             |
|                                        | X-axis (mm) | Y-axis (mm) |                     | X-axis (mm) | Y-axis (mm) |
| A                                      | +065 (1.65) | +252 (6.40) | K                   | -195 (4.95) | +113 (2.87) |
| B                                      | +195 (4.95) | +113 (2.87) | L                   | -065 (1.65) | +252 (6.40) |
| C                                      | +260 (6.60) | +000 (0.00) | M                   | -065 (1.65) | +113 (2.87) |
| D                                      | +195 (4.95) | -113 (2.87) | N                   | +065 (1.65) | +113 (2.87) |
| E                                      | +130 (3.30) | -225 (5.72) | P                   | +130 (3.30) | +000 (0.00) |
| F                                      | +000 (0.00) | -225 (5.72) | R                   | +065 (1.65) | -113 (2.87) |
| G                                      | -130 (3.30) | -225 (5.72) | S                   | -065 (1.65) | -113 (2.87) |
| H                                      | -195 (4.95) | -113 (2.87) | T                   | -130 (3.30) | +000 (0.00) |
| J                                      | -260 (6.60) | +000 (0.00) | U                   | +000 (0.00) | +000 (0.00) |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 15         | -18             | 18                 | 20            | I              | All              | MS20052-18 |

Panel Cutout



| Dim | Nominal    |
|-----|------------|
| ØA  | 26.59 min  |
| ØAA | 23.01 min  |
| R1  | 24.61      |
| ØT  | 3.25 ±0.13 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D015Z18SE

|                |                                    |                            |                                                                                                       |
|----------------|------------------------------------|----------------------------|-------------------------------------------------------------------------------------------------------|
| A              | 18-10-2016                         | First Release              |                                                                                                       |
| ISS            | DATE                               | Latest modification - by   | MOD N°                                                                                                |
| Designed By:   |                                    | Date:                      | <b>CUSTOMER DRAWING</b>                                                                               |
| <b>TITLE</b>   | Aluminium Receptacle 8D series     |                            |                                                                                                       |
| SCALE          |                                    | General linear Tolerances: | NPRDS / PROJECT                                                                                       |
| NA             |                                    | ±--                        | <b>859</b>                                                                                            |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>             |                            | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D015Z18SE-C</b> |                            | SHEET 2/2                                                                                             |