



Contact Layout

22



2#12  
2#8 Triax

| 17-22 |       |       |
|-------|-------|-------|
| Ctc   | X     | Y     |
| A     | 0     | 4.57  |
| B     | 6.32  | 0     |
| C     | 0     | -4.57 |
| D     | -6.32 | 0     |

Panel Cutout



Max. thickness panel for receptacle: Type 0: front mounting = 3.2 mm, rear mounting = 2.5 mm

| Dim | Nominal    |
|-----|------------|
| ØA  | 30.96 min  |
| ØAA | 25.81 min  |
| R1  | 26.97      |
| ØT  | 3.25 ±0.13 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D017S22AC

|                |   |                            |   |
|----------------|---|----------------------------|---|
| B              | 11-04-17                                    | Drawing Update             |   |
| ISS            | DATE  | Latest modification - by   | MOD N°  |
| Designed By:   |   | Date:                      | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | <b>Stainless Steel Receptacle 8D series</b> |                            |   |
| SCALE          |   | General linear Tolerances: | NPRDS / PROJECT   |
| NA             |   | ±--                        | <b>859</b>  |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                      |                            | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D017S22AC-C</b>          |                            | SHEET 2/2   |