





LAYOUT SHOWN AS

Keying Shown as example

CHARACTERISTICS

BASIC SERIES:

SHELL SIZE : 19

PLATING : F = Nickel

Н

SHELL TYPE : Square Flange Receptacle

CONTACT TYPE : Standard Crimp Contact

ယ

 \sim

-Standard : Based on MIL-DTL-38999 Series III

-Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy : Silicon Elastomer -Seals & Grommet -Contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories : -65°C to +200°C -Temperature Range -Salt Spray : 48 hours -Mass : 44.66 g ± 10%

8D 0

G

19

F

11

S

F

С


Dim	Nominal	
Р	3.25±0.2	
PP	4.93±0.2	
R1	29.36	
R2	26.97	
S	36.5±0.3	
V	20.83+0/-1.25	
W	2.1/2.5	
Z	31.5 Max	
/V THREAD	M28x1-6g	

ORIENTATION : C

CONTACT LAYOUT : 19-11

CONTACT TYPE : SOCKET(500 Matings)

Е





σ		A			
				4	
AS EXAMPLE				3	
r any non-conformit s which does not co er of the Parties or b ndation, technical n Juntry Jurisc FR JPF11SC	mply with by a third part			2	
	CUSTOME	R DRAWING	MOD N°		
um Receptacle 8D series					
ar :	NPRDS / PROJECT 859				
J.COM	communicated without permission				
U DRG N° 9F11SC-C			SHEET		
B		A	÷/ ÷	J	
_					

