



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Aluminium
- Shell Plating : Black Zinc Nickel
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered with Souriau contacts and Accessories
- Temperature Range : -65°C to +175°C
- Salt Spray : 500 hours
- Mass : 47.04 g ± 10%

| Connector dimension |               |
|---------------------|---------------|
| Dim                 | Nominal       |
| P                   | 3.25±0.2      |
| PP                  | 4.93±0.2      |
| R1                  | 29.36         |
| R2                  | 26.97         |
| S                   | 36.5±0.3      |
| V                   | 20.83+0/-1.25 |
| W                   | 2.1/2.5       |
| Z                   | 31.5 Max      |
| VV THREAD           | M28x1-6g      |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

|         |                             |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR      | Not Listed                  |

**PN: 8D019Z35BA**

|   |                                    |                                |                               |
|---|------------------------------------|--------------------------------|-------------------------------|
| A   | 02-11-2016                         | First Release                  |                               |
| ISS   | DATE                               | Latest modification - by       | MOD N°                        |
| Designed By:  |                                    | Date:                          | <b>CUSTOMER DRAWING</b>       |
| <b>TITLE</b>  |                                    | Aluminium Receptacle 8D series |                               |
| SCALE   | NA                                 | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b> |
| <b>SOURIAU</b>  |                                    | <b>WWW.SOURIAU.COM</b>         |                               |
| This document is the property of SOURIAU it must not be reproduced or communicated without permission |                                    |                                |                               |
| FORMAT  | <b>SOURIAU DRG N° 8D019Z35BA-C</b> |                                | SHEET<br>1/2                  |

BASIC SERIES: 8D 0 - 19 Z 35 B A

SHELL TYPE : Square Flange Receptacle

CONTACT TYPE : Standard Crimp Contact

SHELL SIZE : 19

PLATING : Z = Black Zinc Nickel

ORIENTATION : A

CONTACT TYPE : SOCKET(500 Matings)

CONTACT LAYOUT : 19-35

Contact Layout



| Contacts<br>(Insert arrangement 19-35) |             |             |                     |             |             |
|--|-------------|-------------|---------------------|-------------|-------------|
| Contact position ID                    | Location    |             | Contact position ID | Location    |             |
|  | X-axis (mm) | Y-axis (mm) |                     | X-axis (mm) | Y-axis (mm) |
| 1                                      | -357 (9.07) | +090 (2.29) | 34                  | +045 (1.14) | +360 (9.14) |
| 2                                      | -357 (9.07) | +000 (0.00) | 35                  | +045 (1.14) | +270 (6.86) |
| 3                                      | -357 (9.07) | -090 (2.29) | 36                  | +045 (1.14) | +180 (4.57) |
| 4                                      | -279 (7.09) | +225 (5.72) | 37                  | +045 (1.14) | +090 (2.29) |
| 5                                      | -279 (7.09) | +135 (3.43) | 38                  | +045 (1.14) | +000 (0.00) |
| 6                                      | -279 (7.09) | +045 (1.14) | 39                  | +045 (1.14) | -090 (2.29) |
| 7                                      | -279 (7.09) | -045 (1.14) | 40                  | +045 (1.14) | -180 (4.57) |
| 8                                      | -279 (7.09) | -135 (3.43) | 41                  | +045 (1.14) | -270 (6.86) |
| 9                                      | -279 (7.09) | -225 (5.72) | 42                  | +045 (1.14) | -360 (9.14) |
| 10                                     | -201 (5.11) | +270 (6.86) | 43                  | +123 (3.12) | +315 (8.00) |
| 11                                     | -201 (5.11) | +180 (4.57) | 44                  | +123 (3.12) | +225 (5.72) |
| 12                                     | -201 (5.11) | +090 (2.29) | 45                  | +123 (3.12) | +135 (3.43) |
| 13                                     | -201 (5.11) | +000 (0.00) | 46                  | +123 (3.12) | +045 (1.14) |
| 14                                     | -201 (5.11) | -090 (2.29) | 47                  | +123 (3.12) | -045 (1.14) |
| 15                                     | -201 (5.11) | -180 (4.57) | 48                  | +123 (3.12) | -135 (3.43) |
| 16                                     | -201 (5.11) | -270 (6.86) | 49                  | +123 (3.12) | -225 (5.72) |
| 17                                     | -123 (3.12) | +315 (8.00) | 50                  | +123 (3.12) | -315 (8.00) |

| Contacts<br>(Insert arrangement 19-35) |             |             |                     |             |             |
|--|-------------|-------------|---------------------|-------------|-------------|
| Contact position ID                    | Location    |             | Contact position ID | Location    |             |
|  | X-axis (mm) | Y-axis (mm) |                     | X-axis (mm) | Y-axis (mm) |
| 18                                     | -123 (3.12) | +225 (5.72) | 51                  | +201 (5.11) | +270 (6.86) |
| 19                                     | -123 (3.12) | +135 (3.43) | 52                  | +201 (5.11) | +180 (4.57) |
| 20                                     | -123 (3.12) | +045 (1.14) | 53                  | +201 (5.11) | +090 (2.29) |
| 21                                     | -123 (3.12) | -045 (1.14) | 54                  | +201 (5.11) | +000 (0.00) |
| 22                                     | -123 (3.12) | -135 (3.43) | 55                  | +201 (5.11) | -090 (2.29) |
| 23                                     | -123 (3.12) | -225 (5.72) | 56                  | +201 (5.11) | -180 (4.57) |
| 24                                     | -123 (3.12) | -315 (8.00) | 57                  | +201 (5.11) | -270 (6.86) |
| 25                                     | -045 (1.14) | +360 (9.14) | 58                  | +279 (7.09) | +225 (5.72) |
| 26                                     | -045 (1.14) | +270 (6.86) | 59                  | +279 (7.09) | +135 (3.43) |
| 27                                     | -045 (1.14) | +180 (4.57) | 60                  | +279 (7.09) | +045 (1.14) |
| 28                                     | -045 (1.14) | +090 (2.29) | 61                  | +279 (7.09) | -045 (1.14) |
| 29                                     | -045 (1.14) | +000 (0.00) | 62                  | +279 (7.09) | -135 (3.43) |
| 30                                     | -045 (1.14) | -090 (2.29) | 63                  | +279 (7.09) | -225 (5.72) |
| 31                                     | -045 (1.14) | -180 (4.57) | 64                  | +357 (9.07) | +090 (2.29) |
| 32                                     | -045 (1.14) | -270 (6.86) | 65                  | +357 (9.07) | +000 (0.00) |
| 33                                     | -045 (1.14) | -360 (9.14) | 66                  | +357 (9.07) | -090 (2.29) |

| (Applicable to MIL-DTL-38999 only) |                 |                    |               |                |                  |            |
|------------------------------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| Shell size                         | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
| 19                                 | -35             | 66                 | 22D           | M              | All              | MS27530-35 |

Panel Cutout



| Dim | Nominal    |
|-----|------------|
| ØA  | 32.94 min  |
| ØAA | 28.98 min  |
| R1  | 29.36      |
| ØT  | 3.25 ±0.13 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D019Z35BA

|                |                                    |                                |   |
|----------------|------------------------------------|--------------------------------|---|
| A              | 02-11-2016                         | First Release                  |   |
| ISS            | DATE                               | Latest modification - by       | MOD N°  |
| Designed By:   |                                    | Date:                          | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   |                                    | Aluminium Receptacle 8D series |   |
| SCALE          | NA                                 | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b>   |
| <b>SOURIAU</b> |                                    | WWW.SOURIAU.COM                |   |
|                |                                    |                                | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D019Z35BA-C</b> |                                | SHEET<br>2/2  |