
—	G	т	m	0







Keying Shown as example

CHARACTERISTICS

ယ

-Standard : Based on MIL-DTL-38999 Series III

CONTACT TYPE : Standard Crimp Contact

SHELL SIZE : 21

PLATING : S = Nickel

Н

\square	– -Shell Material	: Stainless Steel	Р	3.25±0.
			РР	4.93±0.
	-Shell Plating	: Nickel	R1	31.75
	-Insulator	: Thermoplastic	R2	29.36
	-Contacts	: Copper Alloy	S	39.7±0.
			V	20.07+0/-
	-Seals & Grommet	: Silicon Elastomer	W	2.1/3.2
N	-Contact Plating	: Gold over copper Alloy 0.8µm minimum	Z	31.5 Ma
	-Durability	: 500 Mating cycles	VV THREAD	M31x1-
	-Delivered with Souria	u contacts and Accessories		
	-Temperature Range	: -65°C to +200°C		
	-Salt Spray	: 500 hours		
_	-Mass	: 100.9 g ± 10%		
	BASIC SERIES:	8D 0 - 21 S 39 B E		
_	SHELL TYPE : Square	Flange Receptacle		
	1			

G

F

Connector	r dimension	
Dim	Nominal	
Р	3.25±0.2	
PP	4.93±0.2	SOURIAU shall not be liable f
R1	31.75	due to a use of the Produ
R2	29.36	the Specifications issued by eit
S	39.7±0.3	(professional recomm
V	20.07+0/-1.25	
W	2.1/3.2	
Z	31.5 Max	
HREAD	M31x1-6g	
	• • •	PN: 8D0

ORIENTATION : E

CONTACT LAYOUT : 21-39

CONTACT TYPE : SOCKET(500 Matings)

Е



C		Φ			А	•	_
		P					4
LAY	YOUT SHOWN	AS EXAMPLE	0				3
due to a use Specifications	of the Production of the Production of the Product	for any non-conf cts which does n her of the Partie endation, techn	ot comply es or by a t	with hird party	,		
	C	Country . FR	Jurisdictio No	n & Contr ot Listed	ol List		2
PN: 8D021S39BE							
Release							
est modificatio	on - by					MOD N°	
Date:	Stainless	s Steel Rece			DRAWING		-
\bigcirc	General linear NPRDS / PROJECT Tolerances: ± 859				1		
WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission							
		AU DRG				SHEET	
	8002	1S39BE-0	L			1/2	
С		В			A		

