
Ŧ	G	т	m	O







Keying Shown as example

CHARACTERISTICS

ယ

-Standard : Based on MIL-DTL-38999 Series III

CONTACT TYPE : Standard Crimp Contact

SHELL SIZE : 21

PLATING : S = Nickel

Н

		The Bire 50555 beries in						
\square	– -Shell Material	: Stainless Steel						
		РР						
	-Shell Plating	: Nickel R1						
	-Insulator	: Thermoplastic R2						
	-Contacts	: Copper Alloy	20					
	-Seals & Grommet	: Silicon Elastomer W	20.					
\sim	-Contact Plating	: Gold over copper Alloy 0.8µm minimum Z	:					
	-Durability	: 500 Mating cycles VV THREA	DN					
	-Delivered without So	uriau contacts						
	-Temperature Range	-65°C to +200°C						
	-Salt Spray	500 hours						
	-Mass	: 80.08 g ± 10%						
	BASIC SERIES:	8D 0 - 21 S 41 S B L						
_	SHELL TYPE : Square	Flange Receptacle						

G

F

Connector	dimension				
Dim	Nominal				
Р	3.25±0.2				
PP	4.93±0.2				
R1	31.75				
R2	29.36				
S	39.7±0.3				
V	20.07+0/-1.25				
W	2.1/3.2				
Z	31.5 Max				
THREAD	M31x1-6g		Γ		
		ſ	L	1	_
			А	03-11-2016	
				1	

Delivered W/O Contacts

CONTACT LAYOUT : 21-41

CONTACT TYPE : SOCKET(500 Matings)

Е

ORIENTATION : B

D

First Release ISS DATE Latest modification - by Designed By: Date: TITLE Stainless S SCALE General linea Tolerances: \oplus NA ±---**SOURIAU** WWW.SOURIAU SOURIA FORMAT A3 8D0219

0		Φ	P	>		
					4	
LAY	YOUT SHOWN AS EX	AMPLE			3	
SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)						
FR Not Listed PN: 8D021S41SBL						
First Release Latest modificatio	n - by			MOD N°		
Date:	Stainless Stee	el Recepta	customer drawing acle 8D series	; 		
$\exists \bigoplus$	General linear Tolerances: ±	NPRDS / PROJECT 859				
WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission						
	SOURIAU 8D021S4			SHEET		
С		В	A	L	L	

	Т	Q	IL	т	D	0	
		Contact Layout				Ρ	anel Cutout
4	<	31° 23 37° 41'			8	SQUARE FLANGE RECEPTACLE (TYPE 0) REAR MOUNTING	2
		1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1			<u>¥</u>	ØA.	ØT
ω	Shell Arrangement Numb size no. cont 21 -41 4:	acts contacts rating location				Dim ØA ØAA R1 ØT	
	_						
	9					SOURIAU shall not be lia due to a use of the Pr the Specifications issued b (professional reco	roducts whi
N							Country FR
						PN: 81	D02154
					A 03-11-	2016 First Release	
					ISS DAT Designed By:	E Latest modification - by Date:	
					TITLE	Stain	less Ste
_					SCALE NA		eral linear erances: ±
					SOURI	WWW.SOU	RIAU.CO
					FORMAT A3		JRIAU 021S4
	Н	G	F	E	D	C	

