

C)







LAYOUT SHOWN AS

Keying Shown as example

CHARACTERISTICS

-Salt Spray

BASIC SERIES:

SHELL SIZE : 21

PLATING : S = Nickel

Н

SHELL TYPE : Square Flange Receptacle

CONTACT TYPE : Standard Crimp Contact

ယ

 \sim

-Standard : Based on MIL-DTL-38999 Series III

-Shell Material : Stainless Steel -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer : Gold over copper Alloy 0.8µm minimum -Contact Plating -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +200°C

: 500 hours

8D 0

G

21

S

42

В


F

D

Connector dimension Dim Nominal 3.25±0.2 Р PP 4.93±0.2 31.75 R1 29.36 R2 S 39.7±0.3 V 20.07+0/-1.25 W 2.1/3.2 31.5 Max Ζ VV THREAD M31x1-6g

Е

SOURIAU shall not be liable for due to a use of the Products the Specifications issued by either (professional recomment



	Φ		A			
	R				4	
as exa	AMPLE				3	
s which er of t indatic untry FR	non-conformit ch does not co che Parties or b on, technical no Jurisd	mply with by a third part			2	
					-	
		CUSTOME	R DRAWING	MOD N°		
Steel Receptacle 8D series						
ar :			['] PROJECT 59		1	
J.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission						
	DRG N° 2BD-C			SHEET		
	B		A		J	

	т	۵	וד	т	D		0	
		Contact Layout					Ра	nel Cutou
		42				SQL	JARE FLANGE RECEPTACLE (TYPE 0) REAR MOUNTING	
4		, ,						2
		2#4 Power						
	Ctc A B	21-42 X Y 0 6.19 0 -6.19						<u>.T</u>
							Dim ØA	
ယ							ØAA R1	
							ØT	
	-				[
	•						SOURIAU shall not be liab due to a use of the Pro the Specifications issued by (professional recor	oducts wh y either of
N								Country
							PN: 8[L
						03-11-2016	First Release	
					ISS	DATE	Latest modification - by	
					Designe		Date:	
						TITLE	Stainl	ess Ste
<u> </u>					SCAL		[(⊕) Toler	al linear rances: ±
						URIAU	WWW.SOUR	
					FORM	AT		DIALL
					A			RIAU 021S4
l	Н	G	F	E	D		C	

