
т	۵	п –	п	0







LAYOUT SHOWN AS

Keying Shown as example

CHARACTERISTICS

BASIC SERIES:

SHELL SIZE : 21

Н

SHELL TYPE : Square Flange Receptacle

CONTACT TYPE : Standard Crimp Contact

PLATING : W = Olive drab Cadmium

ယ

 \sim

-Standard : Based on MIL-DTL-38999 Series III

-Shell Material	: Aluminium				
-Shell Plating	: Olive drab Cadmium				
-Insulator	: Thermoplastic				
-Contacts	: Copper Alloy				
-Seals & Grommet	: Silicon Elastomer				
-Contact Plating	: Gold over copper Alloy 0.8µm minimum				
-Durability	: 500 Mating cycles				
-Delivered without Souriau contacts					
-Temperature Range	65°C to +175°C				
-Salt Spray	: 500 hours				

8D 0

G

21

W

72

Ρ

F

N L

Connector dimension			
Dim	Nominal		
Р	3.25±0.2		
PP	4.93±0.2		
R1	31.75		
R2	29.36		
S	39.7±0.3		
V	20.07+0/-1.25		
W	2.1/3.2		
Z	31.5 Max		
VV THREAD	M31x1-6g		

Delivered W/O Contacts


CONTACT LAYOUT : 21-72

CONTACT TYPE : PIN(500 Matings)

Е

ORIENTATION : N

SOURIAU shall not be liable for due to a use of the Products the Specifications issued by either (professional recommend



	Ξ		A		
					4
AS EXA	AMPLE				3
whice er of t adatio untry R	n, technical n	mply with by a third party	List		2
				MOD N°	-
		CUSTOMER D	RAWING		
um	n Receptacle 8D series				
ar		NPRDS / PR 859	OJECT		1
I.CC	COM This document is the property of SOURIAU it must not be reproduced or communicated without permission				
	J DRG N° SHEET				
N72	2PNL-C		A	1/2	J
	В		A		

	τ	۵	нт — — — — — — — — — — — — — — — — — — —	m	D	0
4		Contact Layout 72				Panel Cutou
	Ctc	2#4 Power 6#16 21-72 X Y			¥	
3	A B C D E F G H	0 6.19 8.5 4.3 6.25 0 8.5 -4.3 0 -6.19 -8.5 -4.3 -6.25 0 -8.5 4.3				Dim ØA ØAA R1 ØT
						SOURIAU shall not be liable for any
N						due to a use of the Products wh the Specifications issued by either of (professional recommendati Country FR PN: 8D021W
					A 03-11-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:
-					SCALE NA	Aluminium General linear Tolerances: ±
					FORMAT A3	J WWW.SOURIAU.C SOURIAU 8D021W7
	Н	G	F	E	D	C

