

CHARACTER

ω

 \sim

_

T G	п	ш		D	0	σ	A		7
		S R1 R2 I I I I I I I I I I I I I I I I I I				OWN AS EXAMPLE			4
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III -Shell Material : Composite -Shell Material : Composite -Shell Plating : Without Plating -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +175°C	Keying Showr	Connector dimension Dim Nominal P 3.25±0.2 PP 4.93±0.2 R1 31.75 R2 29.36 S 39.7±0.3 V 20.07+0/-1.25 W 2.1/3.2 Z 31.5 Max VV THREAD M31x1-6g			due to a use of the Pr the Specifications issued b (professional reco		with hird party		2
-Salt Spray : 2000 hours				ISS DATE Designed By:	16 First Release Latest modification - by Date:		STOMER DRAWING	MOD N°	
BASIC SERIES: 8D 0 - 21 X SHELL TYPE : Square Flange Receptacle - 21 X CONTACT TYPE : Standard Crimp Contact - - - - - - - - - - - - - - X SHELL SIZE : 21 -	42 S A	ORIE CONTACT TYPE : SOCKET(! CONTACT LA		TITLE SCALE NA SOURIA	U WWW.SOUI	erances: ± RIAU.COM	D series NPRDS / PROJECT 859 This document is the prop SOURIAU it must not be reproduce communicated without per	ed or	_ 1
H G	F	E	1	A3		0021X42SA-C	A	1/2	

	工	۵	н п	m		0	
		Contact Layout					Panel Cutou
		42				SQUARE FLANGE RECEPTACLE (TYPE (REAR MOUNTING	
4					1		
		2#4 Power					
	Ctc A B	21-42 X Y 0 6.19 0 -6.19			1	ØA	ØT_
							im ØA
ယ						R	AA R1
						<u> </u>	ĎΤ
\sim	-						
	a					SOURIAU shall not be due to a use of the the Specifications issue (professional n	e Products wh ed by either of
N							Country
						PN:	8D021)
					A 30-09	2016 First Release	
					ISS DA Designed By:	TE Latest modification - by Date:	У
					TITLE	(Composite
					SCALE		eneral linear Tolerances:
-					NA		±
					SOURI	AU WWW.SO	URIAU.C
					FORMAT		DURIAU
			_	- 1	A3		3D021X4
	Н	G	l F	E	D	C	I

