	т (С. 1997) Г. П. 1997 Г. 1977 Г. 197	m		0			
Contract Plating       Connector dimension         Dim       Nonintersion         Contact Plating       Contact Plating         Stalk Grommer       Sill Noning Ordes         Delevered with Souriau contact and Accessories       Noni Listed         Dim       Noni Listed         Dim       Noni Listed         Basic SSRIES:       Bo       0         Basic SSRIES:       Bo       0         SiteL TYPE: Flug with RFI Shielding       Noni Dictor Plating Plating       Noni Dictor Plating Plating         SiteL TYPE: Flug with RFI Shielding       Onit of the rest denemation       Noni Dictor Plating P							
CHARCTERISTICS         Standard: Based on MIL-DTL-38899 Series III         Shell Material       ::::::::::::::::::::::::::::::::::::	ω			LAYOUT SHC	OWN AS EXAMPLE		
BASIC SERIES:       8D       5       09       J       98       J       N         BASIC SERIES:       8D       5       09       J       98       J       N         CONTACT TYPE:       Standard Crimp Contact       000 M*       Standard Crimp Contact       SOURIAU       SOURIAU       NPRDS / PROJECT         SHELL SIZE : 09       PLATING :       J =       ONTACT TYPE : SOCKET (1500 Matings)       SOURIAU       WWW.SOURIAU.COM       This document is the property of sOURIAU perioded or communicated without periodiced or communicated without periodic	<ul> <li>CHARACTERISTICS</li> <li>Standard : Based on ML-DTL-38999 Series III</li> <li>Shell Material : Composite</li> <li>Shell Plating : Olive drab Cadmium</li> <li>Insulator : Thermoplastic</li> <li>Contacts : Copper Alloy</li> <li>Seals &amp; Grommet : Silicon Elastomer</li> <li>Contact Plating : Gold over copper Alloy 0.8µm minimum</li> <li>Durability : 500 Mating cycles</li> <li>Delivered with Souriau contacts and Accessories</li> <li>Temperature Range : -65°C to +175°C</li> </ul>	Connector dimensionDimNominalØS21.8 MaxZ'31.5 Max	A 14-10-2016	due to a use of the Pro the Specifications issued by (professional reco <b>PN: 8</b>	oducts which does not com y either of the Parties or by mmendation, technical not Country Jurisdic FR	nply with y a third party tice.) ction & Control List	
BASIC SERIES:       8D       5       09       J       98       J       N         SHELL TYPE:       Plug with RFI Shielding       00       J       98       J       N       SCALE       NA       SCALE       State	-Salt Spray : 2000 hours						N°
BASIC SERIES:       BD       SD       SD <td></td> <td></td> <td>TITLE</td> <td colspan="3"></td>			TITLE				
CONTACT TYPE : Standard Crimp Contact       ORIENTATION : N       SOURIAU       SOURIAU       SOURIAU         SHELL SIZE : 09       CONTACT TYPE : SOCKET (1500 Matings)       CONTACT LAYOUT : 09-98       FORMAT       SOURIAU ORIENTATION : N       SOURIAU       SOURIAU       SOURIAU       SOURIAU       SOURIAU       SOURIAU       SOURIAU       It must not be reproduced or communicated without permission       CONTACT LAYOUT : 09-98       FORMAT       SOURIAU DRG N°       SHEET		N			rances:	859	
			SOURIAU	WWW.SOUR	RIAU.COM	SOURIAU it must not be reproduced or	
	PLATING : J = Olive drab Cadmium	CONTACT LAYOUT : 09-98					

r	<b></b>	Q	<b></b>	m	D	0
		Contact Layout				
4	-X	$ \begin{array}{c}                                     $				
	Shell Arrangement Numt size no. cont 9 -98 3	+ 005 (1.65) + 0.38 (0.97) + 0.00 (0.00) - 0.75 (1.91) - 0.65 (1.65) + 0.38 (0.97) - 0.65 (1.65) + 0.38 (0.97) - 0.65 (1.65) + 0.038 (0.97)				
ω						
	F					
						SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o (professional recommenda
N						PN: 8D509
					A 14-10-20 ISS DATE Designed By:	16 First Release
					SCALE	Comp General linear
-					NA	Tolerances:
					FORMAT	U WWW.SOURIAU. SOURIAU
l			-		A3	8D509J
	Н	G	F	E	D	C

