| | | | 0 | œ | | |
|--|-----------------------------------|-------------------------|---|-------------------------------|--|-----------|
| Z' | ØS | | | | | |
| | | | LAYOUT SHOW | /N AS EXAMPLE | | |
| | Keying Shown as example | | | | | |
| CHARACTERISTICS | Connector dimension | | | | | |
| Standard : Based on MIL-DTL-38999 Series III | Dim Nominal ØS 21.8 Max | | | | | |
| -Shell Material : Composite -Shell Plating : Nickel -Insulator : Thermoplastic | Z' 31.5 Max VV THREAD M12x1-6g | | SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) | | | |
| -Contacts : Copper Alloy | | | (professional recom | mendation, technical notice.) | | |
| -Seals & Grommet : Silicon Elastomer | | | - | | & Control List Listed | |
| -Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles | | | L | | | |
| -Delivered without Souriau contacts | | | PN: 8D5 | 09M98PEL | | |
| -Temperature Range : -65°C to +200°C | | | 2016 First Release | | | |
| -Salt Spray : 2000 hours | | | | | | |
| Mass : 8.1 g ± 10% | | ISS DAT Designed By: | TE Latest modification - by Date: | CUST | TOMER DRAWING | DD N° |
| | | TITLE | Composite Plug 8D series | | | |
| BASIC SERIES: 8D 5 - 09 N | 1 98 P E L | SCALE | General | linear NI | PRDS / PROJECT | |
| | Delivered W/C | Contacts NA | Tolerar | nces: | 859 | |
| SHELL TYPE : Plug with RFI Shielding | | | · · · | | This document is the property of SOURIAU | |
| SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact | ORIENT | | | | | |
| | ORIENT CONTACT TYPE : PIN(500 | | AU WWW.SOURI | | it must not be reproduced or ommunicated without permission | ı |
| CONTACT TYPE : Standard Crimp Contact | | Matings) | | | it must not be reproduced or ommunicated without permission | n HEET |

| r | 工 | ۵ | т | m | | 0 |
|------------|---|--|---|---|--|---|
| | | Contact Layout | | | | |
| 4 | -X | $ \begin{array}{c} \bullet \\ \bullet $ | | | | |
| | Shell Arrangement Numb size no. 9 -98 3 | + 0.65 (1.65) + .038 (0.97) + .000 (0.00)075 (1.91) 065 (1.65) + .038 (0.97) 065 (1.65) + .038 (0.97) 065 (1.65) + .038 (0.97) | | | | |
| ω | | | | | | |
| | + | | | | | SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o (professional recommenda |
| N | | | | | | Count FR PN: 8D509N |
| | | | | | A 14-10-20 ISS DATE Designed By: | 16 First Release |
| _ _ | | | | | TITLE SCALE NA | Compo General linear Tolerances: |
| | | | | | SOURIA | |
| | | | | | FORMAT A3 | SOURIAU 8D509M |
| L | Н | G | F | E | D | C |

| | 4 | | | | |
|--|----|--|--|--|--|
| | 3 | | | | |
| any non-conformity or damage which does not comply with r of the Parties or by a third party dation, technical notice.) ntry Jurisdiction & Control List R Not Listed | 2 | | | | |
| CUSTOMER DRAWING | J° | | | | |
| NPRDS / PROJECT 859 | | | | | |
| COM This document is the property of SOURIAU it must not be reproduced or communicated without permission | | | | | |
| communicated without permission | | | | | |
| | | | | | |

A

ω