[т <u>Ω</u> т	m		0	œ	A		
4	Z PBQL PBQL PC PC PC PC PC PC PC PC PC PC						4	
ω				LAYOUT SHOWN AS	EXAMPLE		3	
	Keying Sho	own as example						
	CHARACTERISTICS	Connector dimension						
	-Standard : Based on MIL-DTL-38999 Series III	DimNominalØS25 Max						
N	-Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				2		
	Durability : 500 Mating cycles Delivered with Souriau contacts and Accessories PN: 8D511F01AC							
	-Temperature Range -65°C to +200°C		A 15-10-2016	First Release				
	-Salt Spray : 48 hours -Mass : 14.98 g ± 10%		ISS DATE	Latest modification - by		MOD N	1°	
	-iviass . 14.20 g ± 10/0		Designed By:	Date:	CUSTO	MER DRAWING		
		TITLE	TITLE Aluminium Plug 8D series					
_ _	BASIC SERIES: 8D 5 - 11 F 01 A C SHELL TYPE : Plug with RFI Shielding - 11 F 01 A C		SCALE -{	General linear Tolerances:	NPRI	DS / PROJECT 859	1	
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 CONTACT TYPE : PIN(500 Ma			SOURIAU This document is the property of SOURIAU it must not be reproduced or communicated without permission				
	PLATING : F = Nickel CONTACT LAYOUT : 11-01		FORMAT	SOURIAL		SHEET		
			A3		01AC-C	1/2		
				000111				

r	I	G	г	m	D	0
		Contact Layout				
4		01				
	(1#12 11-01	٦			
ω	Ctc A	X Y 0 0				
	+					SOURIAU shall not be liable for an due to a use of the Products wh
N						the Specifications issued by either of (professional recommendat Countr FR
					A 15-10-20 ISS DATE Designed By:	PN: 8D5111
_					TITLE SCALE NA	Alumin General linear Tolerances: ±
					FORMAT A3	SOURIAU
	Н	G	F	E	D AS	8D511F(

