	т <u></u>	m m		0]
Characteristics Selevator								4
Standard: Based on MIL DT.38999 Series II Shell Material :: Munihum Shell Plating :: Mukel Shell Plating :: Nickel -Insulator :: Termoplastic -Contact Plating :: Silcon Elstomer -Soals & Grownet :: Slicon Elstomer -Outact Plating :: Gold over copper Alloy Sham minimum -Soals & Bray :: 48 hours -Delivered with Souriau contacts and Accessories PN: 8DS11F01BC -Temperature Range :: 60's Cto +200'C -Salt Spray :: 48 hours -Mass : 17.92 g ± 10% BASIC SENIES: 80 5 Shell LTYPE : Slandard Crimp Contact Shell LSZE : 11 If the current linear Mast : Contact TYPE :: Standard Crimp Contact Shell SP = Nickel : CONTACT TYPE :: SockeT(SOO Matings) ORIENTATION : C Souriau Www.SOURIAU.COM Stret vis the reporting of the socked or contact </td <td></td> <td>Keying Shown as example</td> <td></td> <td>LAYOU</td> <td>IT SHOWN AS EXAMPLE</td> <td></td> <td></td> <td>3</td>		Keying Shown as example		LAYOU	IT SHOWN AS EXAMPLE			3
Shell Material ∴ Aurinium Z 31 Max Shell Material ∴ Aurinium Z 31 Max Shell Material ∑ 31 Max Source ∑ 1 - Shell Material ∑ 1 - Shell Material ∑ 1 - Shell Material ∑ 1 - Contact S 1 Contact S 1 - Contact S 1 F 01 Source Source - Durability 200 Mating cycles - - - - Temperature Range : 65°C to 1200°C - - - - Sait Spray : 48 hours MOD M - - Mass : 17.92 g ± 10% MOD M - - - SHELL TYPE Stander Grimp Contact 11 F 01 B C - SHELL SIZE : 11 - 0 Basci Cseries - 859 - </th <th></th> <th>Dim Nominal</th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th>		Dim Nominal						
-Contact Plating ::::::::::::::::::::::::::::::::::::	-Shell Plating: Nickel-Insulator: Thermoplastic	Z31 MaxSOURIAU shall not be liable for any non-conformity or damageVV THREADM15x1-6gdue to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party						
- Durability :: 500 Mating cycles - Delivered with Souriau contacts and Accessories - Temperature Range : -65°C to +200°C - Salt Spray :: 48 hours - Mass :: 17.92 g ± 10% BASIC SERIES: 8D SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE<: 11]	2
-Salt Spray : 48 hours -Mass : 17.92 g ± 10% -Mass : 17.92 g ± 10% BASIC SERIES: 8D SHELL TYPE : 11 F 01 BASIC SERIES: 8D SHELL TYPE : Standard Crimp Contact CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 PLATING : F = Nickel	-Durability : 500 Mating cycles			PN	: 8D511F01BC			
-Mass : 17.92 g ± 10% ISS DATE Latest modification - by MOD N ⁴ BASIC SERIES: 8D 5 -11 F 01 B C ITTLE Aluminium Plug 8D series SCALE General linear NPRDS / PROJECT SHELL TYPE : Plug with RFI Shielding -11 F 01 B C ORIENTATION : C SCALE General linear NPRDS / PROJECT CONTACT TYPE : Standard Crimp Contact ORIENTATION : C ORIENTATION : C SOURIAU This document is the property of SOURIAU SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 Matings) FORMAT SOURIAU DRG N° SHEET	-		A	15-10-2016 First Release				_
BASIC SERIES: 8D 5 - 11 F 01 B C C SCALE SCALE NPRDS / PROJECT 859 SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact NR WWW.SOURIAU.COM This document is the property of SOURIAU SHELL SIZE : 11 CONTACT TYPE : CONTACT TYPE CONTACT TYPE SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU PLATING : F = Nickel CONTACT LAYOUT CONTACT LAYOUT SOURIAU DRG N° SHEET					by	CUSTOMER DRAWING	MOD N°	
BASIC SERIES. BD SD SD <td></td> <td></td> <td>1</td> <td colspan="4">TITLE Aluminium Plug 8D series</td> <td></td>			1	TITLE Aluminium Plug 8D series				
CONTACT TYPE : Standard Crimp Contact ORIENTATION : C SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) PLATING : F = Nickel CONTACT LAYOUT : 11-01		01 B C			Tolerances:			-
PLATING : F = Nickel FORMAT SOURIAU DRG N° SHEET	CONTACT TYPE : Standard Crimp Contact		501	JRIAU WWW.So	OURIAU.COM	SOURIAU it must not be reproduc	ed or	
				AT S	OURIAU DRG N°			-
			A3				1/2	

	т	۵	нт —	т	U	0
		Contact Layout				
4		01				
		1#12 11-01	٦			
ω	Ctc A	X Y 0 0				
	-					SOURIAU shall not be liable for any due to a use of the Products wh
N						the Specifications issued by either of (professional recommendat Countr FR
					A 15-10-20 ISS DATE Designed By:	PN: 8D5111
_					TITLE SCALE NA	Alumin General linear Tolerances: ±
					FORMAT A3	J WWW.SOURIAU.C SOURIAU 8D511F0
l	Н	G	F	E	D	C C

