⊥ <u>Ω</u>	m m		0		
ØS-					
			LAYOUT SHOWN AS EXAM	APLE	
	Koving Shown as overable				
CHARACTERISTICS	Keying Shown as example				
-Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal				
	ØS 25 Max Z 31 Max		SOURIAU shall not be liable for any no	n-conformity or damage	
-Shell Plating : Nickel	VV THREAD M15x1-6g		due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party		
-Insulator : Thermoplastic -Contacts : Copper Alloy			(professional recommendation,		
-Seals & Grommet : Silicon Elastomer			Country	Jurisdiction & Control List] _
-Contact Plating : Gold over copper Alloy 0.8µm minimum			FR	Not Listed	
-Durability : 500 Mating cycles			PN: 8D511F01BD		
-Delivered with Souriau contacts and Accessories					
-Temperature Range65°C to +200°C		A 15-10-2016	5 First Release		
-Salt Spray : 48 hours Mass : 17.92 g ± 10%		ISS DATE	Latest modification - by		MOD N°
		Designed By:	Date:	CUSTOMER DRAWING	1
		TITLE	TITLE Aluminium Plug 8D series		
BASIC SERIES: 8D 5 - 11 F	01 B D	SCALE	General linear	NPRDS / PROJECT	
SHELL TYPE : Plug with RFI Shielding		NA	Tolerances:	859	
				This document is the pro	perty of
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11			- SOURIAU WWW.SOURIAU.COIVI it must not be reproduced or		
	CONTACT TYPE : SOCKET(500			communicated without pe	
	CONTACT LAYO	UI:11-01	SOURIAU D	KG N ⁻	SHEET
PLATING : F = Nickel		A3	8D511F01		1/2

_	Ŧ	G	г	m	D	0
		Contact Layout				
4		01				
		1#12	_			
ω	Ctc A	11-01 X Y 0 0				
	_					SOURIAU shall not be liable for an due to a use of the Products wh the Specifications issued by either of (professional recommendat
N						PN: 8D511F
					A 15-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:
_					SCALE NA	Alumin General linear Tolerances: ±
					FORMAT	J WWW.SOURIAU.C
	Н	G	F	E	A3 D	8D511F0

