т Q I	m		0	∞ >	•
			LAYOUT SHOWN AS EXA	IMIPLE .	
Keying	g Shown as example				
CHARACTERISTICS	Connector dimension Dim Nominal				
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Nickel	ØS 25 Max Z 31 Max VV THREAD M15x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party			
-Insulator : Thermoplastic -Contacts : Copper Alloy			(professional recommendatio		
-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum		L	Country FR	Jurisdiction & Control List Not Listed	
-Durability : 500 Mating cycles -Delivered without Souriau contacts			PN: 8D511F0)1SEL	
-Temperature Range65°C to +200°C		A 15-10-2016	5 First Release		
-Salt Spray : 48 hours - Mass : 16.32 g ± 10%		ISS DATE	Latest modification - by		MOD N°
		Designed By:	Date:	CUSTOMER DRAWING	
		TITLEAluminium Plug 8D series			
BASIC SERIES: 8D 5 - 11 F 01 S SHELL TYPE : Plug with RFI Shielding 	E L Delivered W/O Conta	SCALE cts NA	General linear Tolerances:	NPRDS / PROJECT 859	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11	ORIENTATION CONTACT TYPE : SOCKET(500 Matin	N:E SOURIAU This document is the prosperiod N:E SOURIAU SOURIAU it must not be reprodu it must not be reprodu		duced or	
PLATING : F = Nickel	CONTACT TYPE : SOCKET(SOU Mating	—	SOURIAU		SHEET
		A3	8D511F01		1/2
	Ε	D	C		

to the Specifications issued by either or (professional recommendations) PN: 8D511F A 15-10-2015 First Release <u>155 DATE</u> Latest modification - by Designed By: Date: TITLE Alumin SCALE NA Central linear SOURIAU WWW.SOURIAU.CO FORMAT SOURIAU.CO	ſ	工	۵	וד	т	D	0
If I2 If I2 Image: Image of the Product set of			Contact Layout				
II-01 Ctc X Y A 0 0 SURAU shall not be liable for an due to a use of the Products with the Specification size use of the Product use of the Products with the Specification size use of the Products with the Specification size use of the Products with the Specification size use of the Product use of t	4		01				
Co Co Co Co Co Co Co Co Co Co				1			
to the Specifications issued by either or (professional recommendations) PN: 8D511F A 15-10-2015 First Release <u>155 DATE</u> Latest modification - by Designed By: Date: TITLE Alumin SCALE NA Central linear SOURIAU WWW.SOURIAU.CO FORMAT SOURIAU.CO	ω		X Y				
the Specifications issued by either or (professional recommendation) PN: 8D511F A 15-10-2016 First Release ISS DATE Latest modification - by Designed By: Date: TITLE Alumin SCALE General linear TOTMAT SOURIAU.C		-					SOURIAU shall not be liable for any due to a use of the Products wh
A 15-10-2016 First Release ISS DATE Latest modification - by Designed By: Date: TITLE Alumin SCALE NA General linear Tolerances: ± SOURIAU FORMAT SOURIAU.C	N						the Specifications issued by either of (professional recommendat Countr FR
SCALE NA SOURIAU SOURIAU FORMAT SOURIAU						ISS DATE	16 First Release Latest modification - by
SOURIAU WWW.SOURIAU.C	_					SCALE	Alumin General linear Tolerances:
							J WWW.SOURIAU.C
H G F E D C		Н	G	F	E	A3	8D511F0

Φ		A			
				4	
				3	
any non-conformi which does not co r of the Parties or I dation, technical n ntry Jurisc	mply wit by a third otice.)	th			
1F01SEL	Not Li			2	
			MOD N°		
iinium Plug 8D series					
r	NPRDS / PROJECT 859				
COM This document is the property of SOURIAU it must not be reproduced or communicated without permission					
U DRG N° F01SEL-C	1		SHEET		
B		А		J	