ſ	т <u>О</u> т т		0	ت <del>م</del>	>	]
4						4
ω			LAYOUT SHOWN AS EX.	AMPLE		3
	Keying Shown as example					
	CHARACTERISTICS Connector dimension					
-	-Standard : Based on MIL-DTL-38999 Series III Dim Nominal ØS 25 Max					<u> </u>
	-Shell Material : Aluminium   -Shell Plating : Nickel   -Insulator : Thermoplastic	Image: A luminium   Z   31 Max   SOURIAU shall not be liable for any non-conformity or damage     g   : Nickel   VV THREAD   M15x1-6g   due to a use of the Products which does not comply with     : Thermoplastic   : Thermoplastic   the Specifications issued by either of the Parties or by a third party				
	-Contacts : Copper Alloy		(professional recommendation	on, technical notice.)		
	-Seals & Grommet : Silicon Elastomer		Country Jurisdiction & Control List			2
10	-Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles	tact Plating : Gold over copper Alloy 0.8µm minimum				2
	-Delivered with Souriau contacts and Accessories	PN: 8D511F22AC				
	-Temperature Range -65°C to +200°C					-
	-Salt Spray : 48 hours	A 15-10-2016	First Release			
_	-Mass : 14.47 g ± 10%	ISS DATE	Latest modification - by		MOD N°	-
		Designed By:	Date: CUSTOMER DRAWING		j	-
		TITLE	Aluminium Plug 8D series			
_	BASIC SERIES: 8D 5 - 11 F 22 A C   SHELL TYPE : Plug with RFI Shielding - 11 F 22 A C	SCALE	General linear Tolerances:	NPRDS / PROJECT 859		-
	CONTACT TYPE : Standard Crimp Contact ORIENTATION		This document is the property		property of	1
	SHELL SIZE : 11 CONTACT TYPE : PIN(500 Ma		J WWW.SOURIAU.COM it must not be reproduce communicated without per			
	SHELL SIZE : 11 CONTACT TYPE : PIN(500 Matings   PLATING : F = Nickel CONTACT LAYOUT : 11-23		SOURIAU		SHEET	-
		-22 FORMAT A3	8D511F2		1/2	
L	H G F E	D	C	B A		J
			U I		٦	

	<u> </u>	<u>م</u>	п П	m	D	0	
4		Contact Layout 22*					
	Ctc A B C D	X   Y     1.905   1.905     1.905   -1.905     -1.905   -1.905     -1.905   1.905					
						SOURIAU shall not be liable due to a use of the Produ the Specifications issued by ei (professional recomm	ucts w ither o
N						PN: 8D5	Count FR 511
_					A 15-10-201 ISS DATE Designed By:	6 First Release Latest modification - by Date:	
<u> </u>					TITLE SCALE NA	General li Tolerand ±	ces:
					FORMAT	J WWW.SOURIA SOUR	

G

Н

F

Е

A3

D

С

