Ξ	۵	н т	т			0	σ	A	
	Z M Thread	ØS							
ω						LAYOUT SHOWN	AS EXAMPLE		
		Keying Show	wn as example						
CHARACTERISTICS			Connector dimension	_					
-Standard : Based on N	IIL-DTL-38999 Series III		DimNominalØS25 Max	_					
-Shell Material -Shell Plating -Insulator -Contacts	Image: Shell Material : Aluminium Shell Plating : Nickel Insulator : Thermoplastic Contacts : Copper Alloy				SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
-Seals & Grommet	: Silicon Elastomer	mum				Ca		n & Control List t Listed	
-Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories					PN: 8D511F22BA				
-Temperature Range	: -65°C to +200°C				A 15-10-2016	First Release			
-Salt Spray —— -Mass	: 48 hours : 16.89 g ± 10%				ISS DATE Designed By:	Latest modification - by Date:	CU	STOMER DRAWING	MOD N°
					TITLE	Alu	minium Plug 8D s	eries	
BASIC SERIES:	8D 5 - 11	F 22 B A			SCALE -	General lin Tolerance		NPRDS / PROJECT 859	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings)					SOURIAU This document is the property of SOURIAU it must not be reproduced or communicated without permission			lor	
PLATING : F =	Nickel			AYOUT : 11-22	FORMAT	SOURI	AU DRG N°		SHEET
		I			A3		1F22BA-C		1/2

	т	۵	п –	m	D	0
4		Contact Layout 22*				
	Ctc A B	4#22D 11-22 X Y 1.905 1.905 1.905 -1.905				
ω	C D	-1.905 -1.905 -1.905 1.905				
	+					SOURIAU shall not be liable for due to a use of the Products the Specifications issued by either (professional recomment
2						PN: 8D51
					A 15-10-201 ISS DATE Designed By:	.6 First Release Latest modification - by Date:
_					SCALE NA	Alum General linear Tolerances:
					SOURIAL	J WWW.SOURIAU
					FORMAT	SOURIA

G

Н

F

Е

A3

D

С

