<b>ב</b>			0	₩   2	>	
ØS-						
			LAYOUT SHOWN AS EX	AMPLE		
CHARACTERISTICS	Keying Shown as example	_				
-Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal	_				
-Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	ØS25 MaxZ31 MaxVV THREADM15x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer			Country			
Contact Plating : Gold over copper Alloy 0.8μm minimum			FR	Not Listed		
-Durability : 500 Mating cycles -Delivered without Souriau contacts			PN: 8D511F	22SBL		
-Temperature Range : -65°C to +200°C		A 15.10	2016 First Release			
-Salt Spray : 48 hours						
		ISS DAT Designed By:	TE Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	
		TITLE	Alumini	um Plug 8D series		
BASIC SERIES: 8D 5 - 11 F	22   S   B   L	SCALE	General linear	NPRDS / PROJECT		
SHELL TYPE : Plug with RFI Shielding		//O Contacts NA	Tolerances:	859		
SHELL TYPE : Plug with RFI Shielding       Delivered W/O Contact         CONTACT TYPE : Standard Crimp Contact       ORIENTATION :         SHELL SIZE : 11       CONTACT TYPE : SOCKET(500 Mating:			This document is the property of SOURIAU SOURIAU			
					it must not be reproduced or communicated without permission	
		FORMAT	SOURIAU		SHEET	
PLATING : F = Nickel	CONTACT LAY	A3	SUURIAU	DRG N	SHELT	

-	I	G	гт –	m	D	0	
4		Contact Layout 22*					
	Ctc	4#22D 11-22 X Y					
ယ	A B C D	1.905         1.905           1.905         -1.905           -1.905         -1.905           -1.905         1.905	-				
						the Specifications i	of the Products w issued by either
N							Coun FR N: 8D511
					A 15-10-201 ISS DATE Designed By:	.6 First Release Latest modification Date:	
					TITLE SCALE NA		Alumi General linear Tolerances: ±
<u> </u>					FORMAT		SOURIAU.
							JUUKIAL

G

Н

F

Е

A3

D

С

