ב בר	т	m		0	Φ		
				LAYOUT SHOWN AS			
	Keying Shown as examp	le					
-Standard : Based on MIL-DTL-38999 Series III	C	onnector dimension m Nominal					
-Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	S 25 Max 31 Max READ M15x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)					
-Seals & Grommet : Silicon Elastomer				Cou		on & Control List ot Listed	
 -Contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : 500 Mating cycles -Delivered without Souriau contacts 				PN: 8D511			
-Temperature Range : -65°C to +200°C			A 15-10-201	16 First Release			
-Salt Spray : 48 hours 			ISS DATE Designed By:	Latest modification - by Date:	CL	JSTOMER DRAWING	MOD N°
			TITLE	Aluminium Plug 8D s		series	
→ BASIC SERIES: 8D 5 - 11 F SHELL TYPE : Plug with RFI Shielding	98 S B L	Delivered W/O Contacts	SCALE	General linear Tolerances:	r	NPRDS / PROJECT 859	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Mail			B SOURIAU WWW.SOURIAU.COM This document is the property SOURIAU it must not be reproduced on			d or	
PLATING : F = Nickel		CONTACT LAYOUT : 11-98	FORMAT	SOURIA	U DRG N°		SHEET
PLATING . F - NICKEI							

	Ŧ	G	п –	m	D	0
4	-x(Contact Layout $A \oplus B \oplus B \oplus B \oplus C \oplus C \oplus C \oplus C \oplus C \oplus C \oplus C$				
	Cont posit ID A B C C D E F F Shell Arrangement Numb size no. C 11 -98 6	Jon (mm) X-axis (mm) Y-axis (mm) +.000 (0.00) +.130 (3.30) +.130 (3.30) +.000 (0.00) +.130 (3.30) +.000 (0.00) 065 (1.65) 113 (2.87) 056 (1.65) 113 (2.87) 130 (3.30) +.000 (0.00) +.000 (0.00) +.000 (0.00)]			
ى		I MOLOUGO-30				
	-					SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o
27						(professional recommenda Count FR PN: 8D5111
					A 15-10-202 ISS DATE Designed By:	16 First Release
<u> </u>					SCALE NA	Alumir General linear Tolerances: ±
					FORMAT A3	WWW.SOURIAU.C SOURIAU 8D511F9
l	Н	G	F	E	D	C

