ער בייער ביי			0	σ				
A	ØS							
ω			LAYOUT SHO	OWN AS EXAMPLE				
	Keying Shown as example							
 CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III -Shell Material : Composite -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : 500 Mating cycles 	Connector dimensionDimNominalØS25 MaxZ'31.5 MaxVV THREADM15x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed					
-Delivered with Souriau contacts and Accessories			PN: 8D511J01HB					
-Temperature Range : -65°C to +175°C -Salt Spray : 2000 hours		A 15-10-2016 ISS DATE Designed By:	5 First Release Latest modification - by Date:		MOD CUSTOMER DRAWING	N°		
		TITLE		Composite Plug 8D	D series			
ARXIC SERIES: 8D 5 - 11 SHELL TYPE : Plug with RFI Shielding	J 01 H B	SCALE NA	-{	al linear rances: ±	NPRDS / PROJECT 859			
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11	PE : Standard Crimp Contact ORIENTATION : B		SOURIAU WWW.SOURIAU.COM This document so it must not b communicated					
PLATING : J = Olive drab Cadmium	CONTACT LAYOUT	: 11-01 FORMAT A3		RIAU DRG N° 511J01HB-C	SHEE 1/2			
			<u> </u>					

r		т		G		Π	т		D	0	
			Contact Layout	:							
4			01)							
			1#12	/	1						
ω		Ctc A	11-01 X 0	<u>ү</u> 0							
	ŀ									due to a use the Specification	not be liable for an of the Products wh s issued by either of ional recommendat
N											Countr FR
										16 First Release	PN: 8D511J
									ISS DATE Designed By: TITLE	Latest modificati Date:	
<u> </u>									SCALE NA		General linear Tolerances: ±
									FORMAT	U WWW	SOURIAU.C
									A3		SOURIAU 8D511J0
		Н		G		F	E	\mathbf{V}	D	C	

