<u>ت</u>	וד	m	D	0	σ	A	
	N/ Thread						
				LAYOUT SHO	WN AS EXAMPLE		
	Keying Show	n as example					
CHARACTERISTICS		Connector dimension					
		Dim Nominal ØS 25 Max					
-Shell Material : Composite -Shell Plating : Nickel		Z' 31.5 Max		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with			
-Insulator : Thermoplastic		VV THREAD M15x1-6g		the Specifications issued by	either of the Parties or by a t	hird party	
-Contacts : Copper Alloy				(professional record	mmendation, technical notice	.)	
-Seals & Grommet : Silicon Elastomer					Country Jurisdiction	n & Control List	
-Contact Plating : Gold over copper Alloy	0.8μm minimum					t Listed	
-Durability : 500 Mating cycles							
-Delivered with Souriau contacts and Accessories				PN: 8D511M01PA			
-Temperature Range : -65°C to +200°C			A 16-10-201	6 First Release			
-Salt Spray : 2000 hours							
Mass : 12.8 g ± 10%			ISS DATE Designed By:	Latest modification - by Date:	CU	ISTOMER DRAWING	IOD N°
			TITLE	ITLE Composite Plug 8D series		eries	
BASIC SERIES: 8D 5	- 11 M 01 P A	1	SCALE	Genera	al linear	NPRDS / PROJECT	
	- 11 M 01 P A		NA	-[ -(	ances:	859	
SHELL TYPE : Plug with RFI Shielding			_			This document is the property c	of
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11		ORIENTATION :	- SOURIAL	WWW.SOUR		SOURIAU it must not be reproduced or	
	L	CONTACT TYPE : PIN(500 Mating	-			communicated without permission	
PLATING : M = Nickel		CONTACT LAYOUT : 11-0			RIAU DRG N° 511M01PA-C		БНЕЕТ 1/2
1							1111

-	Ŧ	G	н Г	m	D	•
		Contact Layout				
4	/	01				
	(	1#12				
	Ctc A	11-01 X Y 0 0				
ω						
						SOURIAU shall not be liable for an
						due to a use of the Products wh the Specifications issued by either of (professional recommendat
0						PN: 8D511N
					A 16-10-2 ISS DATE	016 First Release
					Designed By:	Date:
<u> </u>					SCALE NA	General linear Tolerances:
					SOURIA	
					FORMAT A3	SOURIAU 8D511M
	Н	G	F	E	D	C

