ב בר	m m		0		
A					
	Keying Shown as example		LAYOUT SHOWN AS EXA	AMPLE	
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III -Shell Material : Composite -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	Connector dimensionDimNominalØS25 MaxZ'31.5 MaxVV THREADM15x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)		
-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles -Delivered without Souriau contacts			Country Jurisdiction & Control List FR Not Listed PN: 8D511M02PDL		
-Temperature Range : -65°C to +200°C -Salt Spray : 2000 hours - Mass : 10.9 g ± 10%		A 16-10-2010 ISS DATE Designed By:	6 First Release Latest modification - by Date:	CUSTOMER DRAWING	
BASIC SERIES: 8D 5 - 11 M SHELL TYPE : Plug with RFI Shielding	02 P D L Delivered W/O Cont		General linear Tolerances: ±	NPRDS / PROJECT 859 This document is the pro	operty of
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11	ORIENTATION CONTACT TYPE : PIN(500 Mati	- SOURIAU	J WWW.SOURIAU.CO	communicated without p	

	工	۵	н т	m		0
		Contact Layout				
4	. x 0 (2)	+Y IB IA +X 95 -Y (2.4imm)				
	Cont positi ID A B Shell Arrangement size no. 11 -2	X-axis Y-axis (mm) (mm) +.095 (2.41) +.000 (.00) 095 (2.41) +.000 (.00)				
ى ع						
	-					SOURIAU shall not be liable for a
						due to a use of the Products w the Specifications issued by either (professional recommenda
N						Count FR
						PN: 8D511N
					A 16-10-20 ISS DATE	116 First Release Latest modification - by
					Designed By:	Date:
					TITLE	Comp
					SCALE NA	General linear Tolerances: ±
					SOURIA	U WWW.SOURIAU.
					FORMAT	SOURIAL
l	Н	G	F	E	A3	8D511M
			· ·	· • \	V	

