			0				
							-
			LAYOUT S	HOWN AS EXAMPLE			
	Keying Shown as example						
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal						
-Shell Material : Composite -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum	ØS25 MaxZ'31.5 MaxVV THREADM15x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed			_	
-Durability : 500 Mating cycles							
-Delivered with Souriau contacts and Accessories			PN: 8D511M22BE				
-Temperature Range : -65°C to +200°C -Salt Spray : 2000 hours		A 16-10-2010	6 First Release				
Mass : 13.8 g ± 10%		ISS DATE				MOD N°	2
					CUSTOMER DRAWING		
		IIILE	TITLE Composite Plug 8D series				
BASIC SERIES: 8D 5 - 11 M SHELL TYPE : Plug with RFI Shielding	22 B E	SCALE NA		neral linear blerances: ±	NPRDS / PROJECT 859		
CONTACT TYPE : Standard Crimp Contact	ORIENTATION : E		This document is the property of SOURIAU				
	CONTACT TYPE : SOCKET(500 Matings)		OUNTAG VV VV.SOURIAU.COIVI it must not be reproduced or communicated without permission				
SHELL SIZE : 11					o	CLIEFT	_
SHELL SIZE : 11 PLATING : M = Nickel	CONTACT LAYOUT : 11-22	FORMAT A3		URIAU DRG N 0511M22BE-C		SHEET	

	工	۵	г	m		0
4		Contact Layout 22*				
		4#22D	7			
ω	Ctc A B C D	X Y 1.905 1.905 1.905 -1.905 -1.905 -1.905 -1.905 1.905				
						SOURIAU shall not be liable for due to a use of the Products the Specifications issued by eithe (professional recommen
0						PN: 8D512
					A 16-10-201 ISS DATE Designed By:	6 First Release Latest modification - by Date:
_					TITLE SCALE NA	Com General linea Tolerances: ±
					SOURIAU	WWW.SOURIAU

G

Н

F

Е

A3

D

С

