ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב			0		A		
Z'	ØS	_					
	I			LAYOUT SHOWN AS EXAMPLE			
	Keying Shown as example						
CHARACTERISTICS	Connector dimen	nsion					
Standard : Based on MIL-DTL-38999 Series III		Nominal 25 Max					
-Shell Material : Composite -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	Z' 3:	11.5 Max Л15x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
-Seals & Grommet : Silicon Elastomer				Country Jurisd	iction & Control List		
-Contact Plating : Gold over copper Alloy 0.8µm minimum		L.		FR	Not Listed		
-Durability : 500 Mating cycles -Delivered without Souriau contacts			PN: 8D511M22SBL				
-Temperature Range65°C to +200°C							
-Salt Spray : 2000 hours		A	16-10-2016 First Release				
Mass : 12.8 g ± 10%		ISS Designed	DATE Latest modifica d By: Dat	-	CUSTOMER DRAWING	MOD N°	
		г	TITLE	Composite Plug 8D se		ries	
BASIC SERIES: 8D 5 - 11 M	22 S B L	SCAL		General linear	NPRDS / PROJECT		
SHELL TYPE : Plug with RFI Shielding		Delivered W/O Contacts NA		Tolerances: ±	859		
CONTACT TYPE : Standard Crimp Contact					This document is the prop SOURIAU	erty of	
SHELL SIZE : 11	CONTACT TYPE	E : SOCKET(500 Matings)		N.SOURIAU.COM	it must not be reproduce communicated without per		
PLATING : M = Nickel		ONTACT LAYOUT : 11-22	AT	SOURIAU DRG N°		SHEET	
		A3	3	8D511M22SBL-C		1/2	

	Т	G	г П	m	D	C	
4		Contact Layout 22*					
	Ctc A B C	4#22D 11-22 X Y 1.905 1.905 1.905 -1.905 -1.905 -1.905					
ى د	D	-1.905 1.905]				
	+					SOURIAU shall not I due to a use of t the Specifications issu (professional	he Products w
S						PN:	Ecount FR 8D511
					ISS DATE Designed By:	6 First Release Latest modification - I Date:	
<u> </u>					SCALE NA		Comp General linear Tolerances: ±
					FORMAT		

G

Н

F

Е

A3

D

С

