	[Т	۵	الت	m			0	œ	A		7
CHARCTENSTCS Standard: Based on MIL-DTI-38999 Series. III Standard: Based on MIL-DTI-3899 Series. III Standard: Based on MIL-DTI-3899 Series. Standard: Based on MIL-DTI-3899 Series. Standard: Based on MIL-DTI-3899 Series. Delivered without Sourisau contacts Temperature Base: Stondard: Based on MIL-DTI-3899 Mass Stondard: Based on MIL-DTI-3899 Stondard: Based on MIL-DTI-3899 Stondard: Based on MIL-DTI-3899 Based Standard: Based on MIL-DTI-3899 Stondard: Based on MIL-DTI-3890 Mass Stondard: Based on MIL-DTI-3890 Mass Stondard: Based on MIL-DTI-3900 Mass Stondard: Based on MIL-DTI-3900 Mass Stondard: Based on MIL-DTI-3900 Mass Stondard: Ching Contact Mass Stondard: Ching Contact Mass Stondard: Ching Contact Mass Stondard: Ching Contact	4		__ _ __ _ __ _ __ _ __ _ _ 									4
CHARCTERISTICS Standard : Based on MIL-DTL-38099 Series II Shell Material ::::::::::::::::::::::::::::::::::::	ω							LAYOUT SHO	WN AS EXAMPLE			3
CHARACTERISTICS Standard: Based on ML-DTL-38999 Series II Shell Material ::::::::::::::::::::::::::::::::::::				Keving Sh	nown as example							
Standard : Based on MIL-DTL-38999 Series III Standard : Based on MIL-DTL-3899 Series I		CHARACTERISTICS		,		-						
Shell Material : Aluminium Shell Material : Aluminium Shell Material : Aluminium Shell Material : Contracts Shell Material : Contracts : Contracts : Coper Aloy Seals & Grommet : Slicon Elastomer - Ontract Plang : Gold over coper Alloy 0.8µm minimum - Oritacts : Subolation in the Specifications issues of the Products which does not comply with the Specifications issues of the Products which does not comply with the Specifications issues of the Products which does not comply with the Specifications issues of the Products which does not comply with the Specifications issues of the Products which does not comply with the Specifications issues of the Products which does not comply with the Specifications issues of the Products which does not comply with the Specifications issues of the Products which does not comply with the Specifications issues of the Products which does not comply with the Specifications issues of the Products which does not comply with the Specifications issues of the Products which does not comply with the Specifications issues of the Products which does not comply with the Specifications issues of the Products which does not comply with the Specifications issues of the Products which does not comply with the Specifications issues of the Products which does not comply with the Specifications issues of the Products which does not comply with the Specifications issues of the Products which does not comply with the Specifications issues of the Products which does not comply with the Specifications issues of the Products which does not comply with the Specifications is			-DTL-38999 Series III		Dim Nominal							
 Contact Plating :: Gold over copper Alloy 0.8µm minimum Durability :: 500 Mating cycles Delivered without Souriau contacts Temperature Range :: -65°C to +175°C Salt Spray :: 500 hours -Mass :: 16.04 g ± 10% BASIC SERIES: <u>8D</u> 5 - 11 W 05 S C L BASIC SERIES: <u>8D</u> 5 - 11 W 05 S C L BASIC SERIES: <u>8D</u> 5 - 11 W 05 S C L Delivered W/O Contact Delivered W/O Contact ORIENTATION : C SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 PLATING : W = 0 live drab Cadmium 		Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic			oducts which does not con a either of the Parties or by	comply with r by a third party						
-Durability : 500 Mating cycles -Delivered without Souriau contacts -Temperature Range : 65°C to +175°C -Salt Spray : 500 hours -Mass : 16.04 g ± 10% BASIC SERIES: 8D 5 SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11	\sim			ninimum								2
-Salt Spray :: 500 hours -Mass :: 16.04 g ± 10% BASIC SERIES: 8D 5 - 11 W 05 S C L SHELL TYPE : Standard Crimp Contact SHELL SIZE : 11 PLATING :: W = Olive drab Cadmium 05 CONTACT TYPE : SOCKET(500 Matings) PLATING :: W = Olive drab Cadmium 05 CONTACT LAYOUT : 11:05 CONTACT TYPE :: Standard Crimp Contact SHELL SIZE : 11 PLATING :: W = Olive drab Cadmium 05 CONTACT LAYOUT : 11:05		-Durability :	500 Mating cycles					PN: 8D	511W05SCL			
- Mass : 16.04 g ± 10% - MoD N ^o - Delivered W/O Contact - SHELL TYPE : Plug with RFI Shielding - CONTACT TYPE : Standard Crimp Contact - SHELL SIZE : 11 - PLATING : W = Olive drab Cadmium - CONTACT TYPE : SOCKET(500 Matings) - PLATING : W = Olive drab Cadmium - CONTACT LAYOUT : 11-05 - C							A 17-10-2016	6 First Release			1	-
Mind Designed By: Date: CUSTOMER DRAWING BASIC SERIES: 8D 5 11 W 05 S C L BASIC SERIES: 8D 5 - 11 W 05 S C L SCALE General linear Tolerances: ± NPRDS / PROJECT 859 5 559 5 11 W 05 S C L CONTACT TYPE : Standard Crimp Contact: NPRDS / PROJECT 859 5 50URIAU This document is the property of SOURIAU. SOURIAU 11 Not be reproduced or communicated without permission SOURIAU This document is the property of SOURIAU. SOURIAU 11 Not be reproduced or communicated without permission SOURIAU Not be reproduced or communicated without permission SOURIAU FORMAT SOURIAU DRG N° SHEET							ISS DATE	Latest modification - by			MOD N°	
BASIC SERIES: 8D 5 - 11 W 05 S C L L SALL SALL Delivered W/O Contacts SALL NPRDS / PROJECT 859 1 NPRDS / PROJECT 859 1 NA Image: Contacts SASIC SERIES: 1 1 Na Image: Contacts 1 Na Image: Contacts 1 Na 1 1										CUSTOMER DRAWING		_
A SAC SERIES. BASIC SERIES. BASIC SERIES. BASIC SERIES. BASIC SERIES. Image: Masic series se						TITLE Aluminium Plug 8D series						
CONTACT TYPE : Standard Crimp Contact ORIENTATION : C SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 11-05 FORMAT SOURIAU SOURIAU SOURIAU SOURIAU SOURIAU SOURIAU SOURIAU SOURIAU SOURIAU				11 W 05 S		W/O Contacts		-[(ances:			1
PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 11-05 FORMAT SOURIAU DRG N° SHEET						SOURIAU WWW.SOURIAU.COM SOURIAU it must not be reproduced or			ed or			
			ive drah Cadmium	└			FORMAT			communicated without pe		_
		LATING . W = UI		I	CONTACT LA	1						
H G F E D C B A	L	Н	G	F	E	1				A		

-	Ŧ	۵	н г	m		0
		Contact Layout				
4	- <u>×</u>	$ \begin{array}{c} & & \\ & & \\ & \\ & \\ & \\ & \\ & \\ & \\ & $				
	Shell Arrangement Numb-	n X-axis Y-axis (mm) (mm) +.065(1.65) +.056(1.42) +.113(2.87)065(1.65) +.000(0.00)130(3.30) 113(2.87)065(1.65) 065(1.65) +.056(1.42) er of Size Service Contact Supersedes tots contacts rating location]			
ى	11 -5 5	20 I All MS20050-5	I			
						SOURIAU shall not be liable for ar due to a use of the Products w the Specifications issued by either o (professional recommenda
23						Count FR
					ISS DATE	-
					Designed By: TITLE SCALE	Date:
_					NA	General linear Tolerances: ±
					FORMAT	SOURIAU
	Н	G	F	E	A3	8D511W

σ							
				4			
				3			
R	ot comply with or by a third cal notice.) urisdiction & Not Li	th d party Control List		2			
W05SCL			MOD N°	-			
ninium Plug 8D series							
ır	r NPRDS / PROJECT 859						
.COM	.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission						
U DRG N V05SCL-			SHEET 2/2	-			
B	<u> </u>	A		J			