I	т р т	т	D	0	Φ	A	7
4							4
ယ				LAYOUT SHOWN AS EXA	AMPLE		3
	Keying Sh	own as example					
	CHARACTERISTICS	Connector dimension					
	-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal ØS 25 Max					
2	-Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
	Image: Sold over copper Alloy 0.8µm minimum FR Not Listed urability : 500 Mating cycles PN: 8D511W05SN elivered with Souriau contacts and Accessories PN: 8D511W05SN					·	2
	-Temperature Range : -65°C to +175°C		A 17-10-2016	6 First Release			1
	-Salt Spray : 500 hours -Mass : 18.04 g ± 10%		ISS DATE	Latest modification - by		MOD N°	_
	101035 . 10.07 B - 10/0		Designed By:	Date:	CUSTOM	ER DRAWING	
TITLE Aluminium Plug 8				um Plug 8D series			
_	BASIC SERIES: 8D 5 - 11 W 05 S SHELL TYPE : Plug with RFI Shielding	N	SCALE NA	General linear Tolerances:		/ PROJECT 859	1
	CONTACT TYPE : Standard Crimp Contact ORIENTATION : N			SOURIAU This document is the property of SOURIAU it must not be reproduced or communicated without permission			
	SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 11-05			COLIDIALL		SHEET	_
	PLATING : W = Olive drab Cadmium	CONTACT LAYOU	A3	SOURIAU 8D511W0		1/2	
			,	ODDITINC	7-NICC	-/-	

-	Ŧ	۵	וד	m		0	
		Contact Layout					
4	-×_	$ \begin{array}{c} & & \\ & \\ & \\ & \\ & \\ & \\ & \\ & \\ & \\ $					
	Shell Arrangement Numt size no.	+.065 (1.65) +.056 (1.42) +.113 (2.87)065 (1.65) +.000 (0.00)130 (3.30) 113 (2.87)065 (1.65) 065 (1.65) +.056 (1.42) Deer of Size Service Contact Supersedes acts contacts rating location]				
ω	11 -5 5	5 20 I All MS20050-5					
	L						
						SOURIAU shall not be liab due to a use of the Pro the Specifications issued by (professional recor	oducts w y either o
N							Count FR
						PN: 8D	0511\
					A 17-10-20 ISS DATE Designed By:	116 First Release Latest modification - by Date:	
					TITLE	4	Alumir
					SCALE NA	-{	al linear rances: ±
					SOURIA	U WWW.SOUR	RIAU.(
					FORMAT A3	SOU 8D5	RIAU
L	Н	G	F	E	D	С	

