Ξ		ഹ	п –		ш	D	0	σ	Þ		٦
		V Thread	ØS								_
•							LAYOUT SH	OWN AS EXAMPLE			
			Keying Sl	hown as example							
CHARACTERIS	TICS			Connec	tor dimension						
-Standard : Bas	ed on MIL-DTL-38999 Ser	ies III		Dim	Nominal						
-Shell Material -Shell Plating -Insulator -Contacts	Image: Description Image: Comparison of the model Image: Comparison of the model Image: Description of the model Image: Comparison of the model Image: Comparison of the model Image: Description of the model Image: Comparison of the model Image: Comparison of the model Image: Description of the model Image: Comparison of the model Image: Comparison of the model Image: Description of the model Image: Comparison of the model Image: Comparison of the model Image: Description of the model Image: Comparison of the model Image: Comparison of the model Image: Description of the model Image: Comparison of the model Image: Comparison of the model Image: Description of the model Image: Comparison of the model Image: Comparison of the model Image: Description of the model Image: Comparison of the model Image: Comparison of the model Image: Description of the model Image: Comparison of the model Image: Comparison of the model Image: Description of the model Image: Comparison of the model Image: Comparison of the model Image: Description of the model Image: Comparison of the model Image: Comparison of the model Image: Description of the model Image: Comparison of the model Image: Comparison of the model Image: Description of the model Image: Comparison of the model Image: Comparison of the mode				SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)						
-Seals & Gromn -Contact Plating		ner per Alloy 0.8μm minim	um					Country Jurisc FR	liction & Control List Not Listed	-	
-Durability	: 500 Mating cyc						PN: 80	0511W05SNL			
-Temperature F	out Souriau contacts ange <u>:</u> -65°C to +175°	°C									_
-Salt Spray	: 500 hours	-				A 17-10-2	2016 First Release				
– -Mass	: 16.04 g ± 10%					ISS DATE Designed By:	E Latest modification - by Date:		CUSTOMER DRAWING	MOD N°	,
				TITLE	Aluminium Plug 8D series						
	0	0 5 - 11	W 05 S	NL		SCALE	Gene	eral linear	NPRDS / PROJECT		_
BASIC SERIES:	lug with RFI Shielding	<u> </u>	W 05 S	NL	Delivered W/O Cont			erances: ±	859		
	: Standard Crimp Cont	act			ORIENTATION				This document is the pro SOURIAU	operty of	
SHELL SIZE : 11				CONT	ACT TYPE : SOCKET(500 Mati	— SUURIA	WWW.SOU	RIAU.COM	it must not be reprodu communicated without p		
	V = Olive drab Cadmit	Jm	' <u> </u>		CONTACT LAYOUT : 1		SOL	JRIAU DRG N°		SHEET	—
			I		I	A3		511W05SNL-C		1/2	
					1						

	Ŧ	۵	н г	m		0
		Contact Layout				
4	- <u>×</u>	$ \begin{array}{c} & & \\ & & \\ & \\ & \\ & \\ & \\ & \\ & \\ & $				
	Conta positic ID A B C C D E Shell Arrangement Numb size no. conta	X-axis Y-axis (mm) +0.65 (1.65) +0.56 (1.42) +.113 (2.87) 065 (1.65) +.000 (0.00) 130 (3.30) 113 (2.87) 065 (1.65) 065 (1.65) +.056 (1.42)				
ω	11 -5 5	20 I All MS20050-5				
	-					SOURIAU shall not be liable for ar due to a use of the Products w the Specifications issued by either o (professional recommenda
N						
					A 17-10-20 ISS DATE Designed By:	PN: 8D511V 16 First Release Latest modification - by Date:
					TITLE	Alumir General linear
-					SOURIA	U WWW.SOURIAU.
					FORMAT A3	SOURIAL 8D511W
	Н	G	F	E	D	C

	Ξ			A				
							4	
							3	
	non-conformit							
r of t	h does not co he Parties or b	oy a thir						
datio	on, technical n	otice.)						
intry R	Jurisdiction & Control List Not Listed							
W05SNL								
]			
					N	IOD N°		
		CUST	OMER DR	WING				
ninium Plug 8D series								
ır	NPRDS / PROJECT							
859 This document is the property of								
.CC	M		OURIAU De reproduc					
U DRG N°					9	SHEET		
V05SNL-C 2/2					2/2			
	В			А				