ſ	۳ Q I	m	D	0	Φ		
4	Z						4
ယ				LAYOUT SHO	WN AS EXAMPLE		3
	Keying	g Shown as example					
	CHARACTERISTICS	Connector dimension	1				
	-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal					
	-Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy Cocla & Crement : Silicon Electomer	g : Olive drab Cadmium i: Thermoplastic : Copper Alloy					
N						on & Control List	2
	-Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories PN: 8D!					FR Not Listed	
	-Temperature Range : -65°C to +175°C			2016 First Dalassa			
	-Salt Spray : 500 hours		A 17-10-	-2016 First Release			
\neg	-Mass : 16.89 g ± 10%		ISS DA Designed By:	TE Latest modification - by Date:		MOD N	N°
			TITLE Aluminium Plug 8D series				
_	BASIC SERIES: 8D 5 - 11 W 22 B SHELL TYPE : Plug with RFI Shielding - - 11 W 22 B	A	SCALE	Genera Tolera		NPRDS / PROJECT 859	
	CONTACT TYPE : Standard Crimp Contact ORIENTAT			A SOURIAU WWW.SOURIAU.COM it must not be re		This document is the property of SOURIAU it must not be reproduced or	
	SHELL SIZE : 11	CONTACT TYPE : SOCKET(50				communicated without permission	
	PLATING : W = Olive drab Cadmium	CONTACT LAY	DUT : 11-22 FORMAT A3		RIAU DRG N° 11W22BA-C	SHEET 1/2	
			,	רעוס			

	工	۵	г П	m	D	0		
4		Contact Layout 22*						
 ى	Ctc A B C D	4#22D 11-22 X Y 1.905 1.905 1.905 -1.905 -1.905 1.905 -1.905 1.905						
	+					SOURIAU shall not be li due to a use of the P the Specifications issued (professional rec	Products w by either	
0						PN: 8	Coun FR	
					A 17-10-201 ISS DATE Designed By: TITLE	L6 First Release Latest modification - by Date:	Latest modification - by	
-					SCALE NA SOURIAL		neral linear llerances: ±	
					FORMAT	SO	URIAU	

G

Н

F

Е

A3

D

С

