BASIC SERIES: 8D 5 - 11 W 22 S D L CUSTOMER DRAWING BASIC SERIES: 8D 5 - 11 W 22 S D L SCALE NA TITLE Aluminium Plug 8D series SHELL TYPE : Plug with RFI Shielding Delivered W/O Contacts NA Image: Contact role rances: source of source of communicated without permission 859 SHELL SIZE : 11 SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) WWW.SOURIAU.COM This document is the property of communicated without permission	ـــــــــــــــــــــــــــــ	m	D	0	₩	Þ
LAYOUT SHOWN AS EXAMPLE Keying Shown as example Shell Material ::::::::::::::::::::::::::::::::::::						
CHARACTERISTICS -Standard: Based on ML: CTL:38999 Series II -Shell Material ::::::::::::::::::::::::::::::::::::				LAYOUT SHOWN A	S EXAMPLE	
-Standard : Based on MIL-DTL-38999 Series III Cultimetodium -Standard : Based on MIL-DTL-38999 Series III Cultimetodium -Shell Material : Aluminium Cultimetodium -Shell Plating : Colper Allay : Cultimetodium -Insulator : Thermoplastic Contract Plating : Colper Allay 0.8µm minimum -Contact Plating : Cold over copper Allay 0.8µm minimum Cultimetodium -Outsched without Sourd contracts - -Delivered without Sourd contracts - -Standard : IS.89 g ± 10% PN: 8D511W22SDL Basic Series: 80 5 11 W 22 S D L Contract Type : Standard Crimp Contact 0RIENTATION :: D Contract Crimp Contact NPRDS / PROJECT SOURIAU NPRDS / PROJECT SHELL SIZE : 11 Contract Pre: Standard Crimp Contact Pric standard Crimp Contact Pric standard Crimp Contact Pric docentaries SHELL SIZE : 11 CONTACT TYPE : Standard Crimp Contact Pric docentarie interact NPRDS / PROJECT Contract Pre: Standard Crimp Contact ORIENTATION :: D Contract Pre: Standard Crimp Contact Pric docentarie interact SOURIAU SHELL SIZE : 11 Contract Pre: Standard Crimp Contact <		Keying Shown as example				
-Standard: Based on MIL-DTL-38999 Series III -Shell Material : Aluminium Shell Material : Aluminium -Shell Material : Contacts : Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : S00 Mating cycles -Delivered without Souriau contracts - -Mass : Sis 0.5 °C to 175°C -Sait Spray : S00 hours -Mass : Sis 0.5 °C to 175°C -Sait Spray : S00 hours -Mass : Sis 0.5 °C to 175°C -Sait Spray : S00 hours -Mass : Sis 0.5 °C to 175°C -Sait Spray : S00 hours -Mass : Sis 0.5 °C to 175°C -Sait Spray : S00 hours -Mass : Sis 0.5 °C to 175°C -Sait Spray : S00 hours -Mass : Sise 0.5 °C to 175°C	CHARACTERISTICS	Connector dimensi	n			
Shell Material : Autuminum Shell Plating : Olive drab Camium Shell Plating : Olive drab Camium Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : Solo Mating cycles -Delivered without Souriau contacts - -Temperature Range : -65°C to +175°C -salt Spray : 500 hours -Mass : 15.89 g ± 10% Basic SERIES: 80 5 11 W 22 D L Delivered W/O contact Souriau Contact NPR05 / PROJECT SHELL TYPE : Plug with RFI Shielding - Image Contact Type : Standard Crimp Contact Souriau SHELL SIZE : 11 ORIENTATION : D CONTACT TYPE : SOURIAU.COM Tite exponder of communicated without permission	-Standard : Based on MIL-DTL-38999 Series III	Dim No	minal			
 -Contact Plating :: Gold over copper Alloy 0.8µm minimum -Durability :: 500 Mating cycles -Delivered without Souriau contacts -Temperature Range :: -65°C to +175°C -Sait Spray :: 500 hours -Mass :: 15.89 g ± 10% <u>A</u> 18-10-2016 First Release -Mass :: 15.89 g ± 10% BASIC SERIES: 8D 5 - 11 W 22 S D L <u>BHELL TYPE :: Plug with RFI Shielding SHELL TYPE :: Plug with RFI Shielding <u>SHELL TYPE :: Standard Crimp Contact SHELL SZE :: 11 <u>SHELL SZE :: 11 SHELL SZE :: 11 </u></u></u></u></u></u>	-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy	Z 31	Max	due to a use of the Products the Specifications issued by eithe	which does not comply with r of the Parties or by a third party	
- Ourability : 500 Mating cycles - Delivered without Souriau contacts - Temperature Range : 65°C to +175°C - Salt Spray : 500 hours - Mass : 15.89 g ± 10% BASIC SERIES: 8D SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 W 22 S D L CONTACT TYPE : Standard Crimp Contact NPRDs / PROJECT SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) WWW.SOURIAU.COM This document is the property of communicated without permission		um		Cou		l List
- Temperature Range : -65°C to +175°C - Salt Spray : 500 hours - Mass : 15.89 g ± 10% BASIC SERIES: <u>8D</u> 5 - 11 W 22 S D L <u>BASIC SERIES: 8D</u> 5 - 11 W 22 S D L <u>CONTACT TYPE : Standard Crimp Contact</u> <u>SHELL TYPE : Standard Crimp Contact</u> <u>SHELL SIZE : 11</u> <u>CONTACT TYPE : SOURIAU</u> <u>CONTACT TYPE : </u>	-Durability : 500 Mating cycles			PN: 8D511	W22SDL	
-Salt Spray : 500 hours -Mass : 15.89 g ± 10% BASIC SERIES: 8D 5 - 11 W 22 S D L SHELL TYPE : Standard Crimp Contact SHELL SIZE : 11 V 22 S D L CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 V 22 S D L CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 V 22 S D L CONTACT TYPE : SOCKET(500 Matings)						
-Mass : 15.89 g ± 10% -Mass : 15.89 g ± 10% 			A 18-10-2	016 First Release		
BASIC SERIES: 8D 5 - 11 W 22 S D L SCALe General linear NPRDS / PROJECT SHELL TYPE : Plug with RFI Shielding Delivered W/O Contacts Delivered W/O Contacts NA Image: Contact row row row contact row					CUSTOMER D	MOD N°
BASIC SERIES. SD SD <td></td> <td></td> <td>TITLE</td> <td>Alum</td> <td>iinium Plug 8D series</td> <td></td>			TITLE	Alum	iinium Plug 8D series	
BASIC SERIES. OD SUB (S a construction)			SCALE	General linea		POIECT
CONTACT TYPE : Standard Crimp Contact ORIENTATION : D ORIENTATION : D SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings)						
SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) SOURIAD WWW.SOURIAU.COIVI it must not be reproduced or communicated without permission				·		
		CONTACT TYPE :		WWW.SOURIAU	.COIVI it must no	ot be reproduced or
	PLATING : W = Olive drab Cadmium			SOURIA		SHEET
A3 8D511W22SDL-C 1/2		l	Δ3			1/2

	т	۵		П	m	D	0	
		Contact Layout						
4		22*						
_		4#22D 11-22						
ω	Ctc A B C D	X 1.905 1.905 -1.905 -1.905	Y 1.905 -1.905 -1.905 1.905					
							SOURIAU shall not be lia due to a use of the Pr the Specifications issued b (professional reco	roducts wl by either o
N							PN: 8D	Count FR 0511V
_						A 18-10-20 ISS DATE Designed By:	16 First Release	
						TITLE		Alumir
<u> </u>						SCALE NA	-{	eral linear erances: ±
						SOURIA	U WWW.SOUF	RIAU.(
						FORMAT A3		JRIAU 511W
				_				1

Н

G

F

Е

D

С

	ω	A				
				4		
				3		
				5		
e liable for any non-conformity or damage e Products which does not comply with ed by either of the Parties or by a third party recommendation, technical notice.)						
Country FR	Jurisc	liction & Control List Not Listed]	2		
3D511W2	22SDL					
У		CUSTOMER DRAWING	MOD N°			
Aluminiu	um Plug 8					
eneral linear		NPRDS / PROJECT				
Tolerances: ±		859		1		
		This document is the pro SOURIAU	perty of	'		
URIAU.COIM it must not be reproduced or communicated without permission						
DURIAU I	DRG N°		SHEET			
D511W22SDL-C 2/2						
	В	A				