]	т	Q	г п	m			0	σ	A		
4		Z	ØS								4
ယ							LAYOUT SHO	WN AS EXAMPLE			3
			Keving St	nown as example							
	CHARACTERISTICS		····,···o -·								
	-Standard : Based on N	IL-DTL-38999 Series III		Connector dimension Dim Nominal							
	-Shell Material: AluminiumØS25 Max-Shell Plating: Olive drab CadmiumZ31 Max-Insulator: ThermoplasticVV THREADM15x1-6g-Contacts: Copper Alloy: Copper Alloy				SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)						
N	-Seals & Grommet -Contact Plating	: Silicon Elastomer : Gold over copper Alloy 0.8μm mi	nimum					Country Jurisdi FR	ction & Control List Not Listed		2
	-Durability -Delivered without Sou	: 500 Mating cycles				PN: 8D511W22SEL					
		-65°C to +175°C				A 18-10-201	6 First Release				-
	-Salt Spray -Mass	: 500 hours : 15.89 g ± 10%				ISS DATE	Latest modification - by			MOD N°	
		0.00 0 - 10/0				Designed By:	Date:		CUSTOMER DRAWING	1	
						TITLE	ļ A	Aluminium Plug 80	) series		
_	BASIC SERIES: SHELL TYPE : Plug with		11 W 22 S	E L Delivered	W/O Contacts	SCALE NA		ll linear ances: 	NPRDS / PROJECT <b>859</b>		1
	CONTACT TYPE       : Standard Crimp Contact         SHELL SIZE : 11       CONTACT TYPE : SOCKET(500 Matings)					SOURIAU         This document is the property of SOURIAU           it must not be reproduced or communicated without permission				ced or	
		LL SIZE : 11       CONTACT TYPE : SOCKET(500 Matings)         FING : W = Olive drab Cadmium       CONTACT LAYOUT : 11-22			-				SHEET	ET	
			I			A3		11W22SEL-C		1/2	
L	Н	G	F	E		D	<u> </u>	B	A		

	т	۵	<del>ار</del> (	m	D	0	
4	(	Contact Layout 22* 0 0 0 0 4#22D					
	Ctc A B C	11-22           X         Y           1.905         1.905           1.905         -1.905           -1.905         -1.905					
ω	D	-1.905 1.905					
						SOURIAU shall not be lia due to a use of the Pi the Specifications issued b (professional reco	roducts v by either
N						PN: 80	Coun FR 0511
					A 18-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:	
					SCALE		Alumi eral linear erances:
					SOURIA		± RIAU.
					FORMAT		

A3

С

D

Ň,

Е

Н

G

F

						4		
						3		
ot be liable for any non-conformity or damage of the Products which does not comply with ssued by either of the Parties or by a third party nal recommendation, technical notice.) Country         Jurisdiction & Control List           FR         Not Listed								
I: 8D511W2	22SEL					_		
n - by MOD N CUSTOMER DRAWING					MOD N°	-		
Aluminium Plug 8D series								
General linear Tolerances: ±		NPRDS / PROJECT <b>859</b>						
SOURIAU.CC	M		perty of red or rmission					
SOURIAU I 8D511W2		<u> </u>			SHEET 2/2	-		
	В			А		L		

А

ω