Г	т	۵	г	т			0	Ξ	A		1	
4		Z A Thread	ØS								4	
ω							LAYOUT SHOWN	AS EXAMPLE			3	
			Keying Sho	wn as example								
	CHARACTERISTICS -Standard : Based on MIL-	DTL-38999 Series III		Connector dimension Dim Nominal	\neg							
2	-Shell Plating:-Insulator:-Contacts:-Seals & Grommet:	ØS 25 Max mell Material : Aluminium mell Plating : Black Zinc Nickel sulator : Thermoplastic sontacts : Copper Alloy eals & Grommet : Silicon Elastomer					SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed					
	-Durability : -Delivered with Souriau co	500 Mating cycles ontacts and Accessories					PN: 8D52	11Z01SD			2	
	-	-65°C to +175°C 500 hours				A 18-10-2016	5 First Release					
	-Mass :	17.92 g ± 10%				ISS DATE Designed By:	Latest modification - by Date:	CU	STOMER DRAWING	MOD N°	┢	
						TITLE	Alur	minium Plug 8D se	eries			
_	BASIC SERIES: SHELL TYPE : Plug with R	J	11 Z 01 S D			SCALE NA	General line Tolerances		NPRDS / PROJECT 859			
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 ORIENTATION : D CONTACT TYPE : SOCKET(500 Matings)						SOURIAU WWW.SOURIAU.COM This document is t SOURI it must not be re communicated with					
	PLATING : Z = Bla	ck Zinc Nickel		CONTACT L	AYOUT : 11-01	FORMAT	SOURI	AU DRG N°		SHEET		
L						A3		1Z01SD-C		1/2	J	
	Н	G	l F	E	\vee	D	C	В	I A			

r		т		G	_	п	m		D	0	
			Contact Layout	:							
4			01)							
			1#12	/	1						
ω		Ctc A	11-01 X 0	<u>ү</u> 0							
	ŀ									due to a use the Specification	not be liable for an e of the Products wh is issued by either of sional recommendat
N											Countr FR
									A 18-10-20 ISS DATE	16 First Release	PN: 8D5112
									Designed By:	Date:	
<u> </u>									SCALE NA		General linear Tolerances: ±
									FORMAT	U WWW	SOURIAU.C
									A3		SOURIAU 8D511Z
		Н		G		-	E	\mathbf{V}	D	C	

