	Т	۵	г		т	C		0	σ	Þ	
4											4
ω C			Keyin	ng Shown as example	ector dimension			LAYOUT SH	HOWN AS EXAMPLE		3
-S -S -II -C -S -C	Shell Plating Insulator Contacts Seals & Grommet Contact Plating	IL-DTL-38999 Series III : Aluminium : Black Zinc Nickel : Thermoplastic : Copper Alloy : Silicon Elastomer : Gold over copper Alloy 0.8µr : 500 Mating cycles	n minimum	Dim ØS Z VV THREA	Nominal25 Max31 Max.DM15x1-6g			due to a use of the P the Specifications issued (professional rec	FR No	with hird party	2
-T -S	Delivered with Souriau Temperature Range Salt Spray	contacts and Accessories : -65°C to +175°C : 500 hours : 14.61 g ± 10%					A 18-10-2016 ISS DATE Designed By:		3D511Z02AD	MOD JSTOMER DRAWING	
	BASIC SERIES: HELL TYPE : Plug with CONTACT TYPE : Stan HELL SIZE : 11		11 Z 02 A	D	ORIENTATIO CONTACT TYPE : PIN(500 Ma	<u> </u>	TITLE SCALE NA SOURIAU	Gene Tol	lerances: ±	eries NPRDS / PROJECT 859 This document is the property of SOURIAU it must not be reproduced or communicated without permission	1
PL	PLATING : Z = E	Black Zinc Nickel	F		CONTACT LAYOUT :	: 11-02	FORMAT A3		URIAU DRG N° D511Z02AD-C B	SHEE 1/2 A	

	Ŧ	۵	н г	m		0	
		Contact Layout					
4	. ×. (2)	+Y B A A A A A A A A A A A A A					
	Cont posit ID A B Shell Arrangement size no. 11 -2	tion X-axis Y-axis (mm) (mm) + .095 (2.41) +.000 (.00)					
ω							
	L						
						SOURIAU shall not be liab due to a use of the Pro the Specifications issued by (professional recor	oducts w y either (
N							Count FR
						PN: 80	0511
						116 First Release	
					ISS DATE Designed By:	Latest modification - by Date:	
					TITLE	4	Alumi
_					SCALE NA	-{	ral linear rances: ±
					SOURIA	U WWW.SOUR	RIAU.(
					FORMAT	SOU	IRIAL
		1	Γ	r r	A3	8D5	511Z
	Н	G	l F	E	D	C	

