	т (п		0	Φ	≻	
Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z						
			LAYOUT SHOWN AS	EXAMPLE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III	Dim         Noming           ØS         25 Mag					
-Shell Material : Aluminium -Shell Plating : Black Zinc Nickel	Z 31 M	ax	SOURIAU shall not be liable for a			
-Insulator : Thermoplastic	VV THREAD M15x1	due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party				
-Contacts : Copper Alloy			(professional recommend	ation, technical notice.)		
-Seals & Grommet : Silicon Elastomer			Cour	try Jurisdiction & Control List		
Contact Plating : Gold over copper Alloy 0.8μm minimum			FF			
-Durability : 500 Mating cycles			PN: 8D511Z04SCL			
-Delivered without Souriau contacts						
-Temperature Range65°C to +175°C		A 18-	10-2016 First Release			
-Salt Spray : 500 hours Mass : 16.26 g ± 10%		ISS	DATE Latest modification - by		MOD N°	
		Designed By:		CUSTOMER DRAWI		
		тіті	LE Alumi	Aluminium Plug 8D series		
BASIC SERIES: 8D 5 - 11 Z	04 S C L	SCALE	General linear	NPRDS / PROJEC	r	
		ered W/O Contacts NA	Tolerances:	859		
SHELL TYPE : Plug with RFI Shielding				This document is t		
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11	CONTACT TYPE : SO	ORIENTATION : C SOUR	<b>WWW.SOURIAU.</b>	it must not be re	produced or	
				communicated with	SHEET	
	CONTA	CT LAYOUT : 11-04	SUURIAI	J DRG N°	STEEL	
PLATING : Z = Black Zinc Nickel		A3		04SCL-C	1/2	

ſ		G	г П	m	D	0	
		Contact Layout					
4	-X	$ \begin{array}{c}                                     $					
	Shell Arrangement Numb size no.	X-axis (mm)         Y-axis (mm)           +0.65 (1.65)         +0.65 (1.65)           +0.65 (1.65)         -0.65 (1.65)           -0.65 (1.65)         -0.65 (1.65)           -0.65 (1.65)         +0.65 (1.65)           er of         Size         Service         Contact         Supersedes	1				
ω	11 -4 4		]				
	+					SOURIAU shall not be liab due to a use of the Pro the Specifications issued by	ducts w either c
N						(professional recon PN: 8D	Count FR
					A 18-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:	
<u> </u>					SCALE NA	A Genera Tolera ±	nces:
					SOURIA		
					FORMAT A3	SOU 8D5	
	Н	G	F	E	D	C	

σ		A				
			4			
			3			
any non-conformi which does not co r of the Parties or I dation, technical n ntry Jurisc R 1ZO4SCL	mply with by a third party		2			
	CUSTOMER DRAWIN	MOD N°				
inium Plug 8D series						
r	NPRDS / PROJECT					
859 This document is the property of						
.COM SOURIAU it must not be reproduced or communicated without permission						
U DRG N°		SHEET				
Z04SCL-C	1	2/2				
В	I	A				