ſ	T Q T		0	ω	A	7
4	Z PEQUIT N PEQUIT N PE					4
ω			LAYOUT SHOWN AS EXA			3
	Keying Shown as example					
	CHARACTERISTICS Connector dimension -Standard : Based on MIL-DTL-38999 Series III Dim Nominal					
	-Shell Material : Aluminium ØS 25 Max Z 31 Max		SOURIAU shall not be liable for any r	non-conformity or damage		
	-Shell Plating : Black Zinc Nickel VV THREAD M15x1-6g		due to a use of the Products whic the Specifications issued by either of t			
	-Insulator : Thermoplastic -Contacts : Copper Alloy		(professional recommendatio			
	-Seals & Grommet : Silicon Elastomer		Country	Jurisdiction & Contro	ol List	
\sim	-Contact Plating : Gold over copper Alloy 0.8µm minimum		FR	Not Listed		2
	-Durability : 500 Mating cycles		PN: 8D511Z22PAL			
	-Delivered without Souriau contacts					
	-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours	A 18-10-2016	First Release			
	-Mass : 14.19 g ± 10%	ISS DATE	Latest modification - by		MOD N°	<u> </u>
		Designed By:	Date:	CUSTOMER I	DRAWING	_
		TITLE Aluminium Plug 8D series				
	BASIC SERIES: 8D 5 - 11 Z 22 P A L	SCALE .	General linear Tolerances:	NPRDS / P 859		
_	SHELL TYPE : Plug with RFI Shielding Delivered W/O Contact ODISNITATION	_		t This document is the property of		
	CONTACT TYPE : Standard Crimp Contact ORIENTATION : SHELL SIZE : 11 CONTACT TYPE : PIN(500 Mating	SOURIAU WWW.SOURIAU.COIVI it must not be reproduced			not be reproduced or	
	PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 11-2	-	SOURIAU I		SHEET	_
		A3	8D511Z22		1/2	
1		-	000117777			1

		۵	г	m	D	0	
4		Contact Layout 22*					
	Ctc A B	4#22D 11-22 X Y 1.905 1.905 1.905 -1.905					
ယ	C D	-1.905 -1.905 -1.905 1.905	-				
						SOURIAU shall not be li due to a use of the F the Specifications issued (professional rec	Products w by either
22						PN: 8	Coun FR
					A 18-10-201 ISS DATE Designed By:	6 First Release Latest modification - by Date:	
<u> </u>					TITLE SCALE NA	Gen Tol	Alumi heral linear lerances: ±
					FORMAT		URIAU.
	1					500	

G

Н

F

Е

A3

D

С

