エ の	т (П	D	0	Φ		
						4
↔ CHARACTERISTICS	Keying Shown as example		LAYOUT SHOWN	N AS EXAMPLE		3
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum	Connector dimensionDimNominalØS25 MaxZ31 MaxVV THREADM15x1-6g		the Specifications issued by eit (professional recomm	cts which does not comply w ther of the Parties or by a thin rendation, technical notice.)	ith rd party & Control List	2
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +175°C -Salt Spray : 500 hours -Mass : 16.89 g ± 10%		A 18-10-2016 ISS DATE Designed By:	1	011Z22SN	MOD N FOMER DRAWING	 √°
A BASIC SERIES: 8D 5 - 11 Z 22 SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11	S N ORIENTATION CONTACT TYPE : SOCKET(500 Matin	- SOUKIAU	General lin Toleranc ±	es:	PRDS / PROJECT 859 This document is the property of SOURIAU it must not be reproduced or	1
PLATING : Z = Black Zinc Nickel	CONTACT TYPE : SOCKET(SOU Matin CONTACT LAYOUT : 11-	_		AU DRG N° 1Z22SN-C B	SHEET 1/2	

	т	۵	н т	m	D	C			
4		Contact Layout 22*							
ω	Ctc A B C D	X Y 1.905 1.905 1.905 -1.905 -1.905 -1.905 -1.905 1.905							
	_					SOURIAU shall not be liable for a due to a use of the Products w the Specifications issued by either (professional recommenda			
N						PN: 8	Count FR 3D511		
_					A 18-10-201 ISS DATE Designed By:	L6 First Release Latest modification - by Date:			
<u> </u>					SCALE NA		Alumi leral linear lerances: ±		
					SOURIAU	J WWW.SOU	RIAU.		

G

Н

F

Е

FORMAT

A3

D

С

