ד Q T			0	₿ >	
Z					
			LAYOUT SHOWN AS EXA	AMPLE	
Keying Shown as	example				
CHARACTERISTICS	Connector dimension				
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium	DimNominalØS29.4 Max				
	Z 31 Max VV THREAD M18x1-6g		SOURIAU shall not be liable for any r due to a use of the Products whic		
-Insulator : Thermoplastic			the Specifications issued by either of t	he Parties or by a third party	
-Contacts : Copper Alloy			(professional recommendatio	יוו, נכנוווונמו ווטנונפ.)	
-Seals & Grommet : Silicon Elastomer			Country		
-Contact Plating : Gold over copper Alloy 0.8µm minimum			FR	Not Listed	
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D513F	03PC	
-Temperature Range65°C to +200°C					
-Salt Spray : 48 hours		A 17-10-2016 F	irst Release		
		ISS DATE	Latest modification - by		MOD N°
		Designed By:	Date:	CUSTOMER DRAWING	
		TITLE Aluminium Plug 8D series			
BASIC SERIES: 8D 5 - 13 F 03 P C		SCALE	General linear	NPRDS / PROJECT	
SHELL TYPE : Plug with RFI Shielding		NA t	Tolerances:	859	
CONTACT TYPE : Standard Crimp Contact	ORIENTATION : C		· .	This document is the pro SOURIAU	operty of
SHELL SIZE : 13	CONTACT TYPE : PIN(500 Matings)	SOURIAU	WWW.SOURIAU.CC	it must not be reprodu communicated without pe	
PLATING : F = Nickel	CONTACT LAYOUT : 13-03	FORMAT	SOURIAU I		SHEET
		A3	8D513F0		1/2

ſ		െ	н т	m	D		0	
		Contact Layout						
4		03						
	[3#16 13-03						
	Ctc A B C	X Y 2.39 1.47 0 -2.79 -2.39 1.47						
ω		·						
	L							
							SOURIAU shall not be li due to a use of the F the Specifications issued (professional rec	Products v by either
N								Coun FR
							PN: 8	8D513
							irst Release	
					ISS Designed By		Latest modification - by Date:	
					TIT	LE		Alumi
<u> </u>					SCALE NA			eral linear lerances: ±
					SOUF	VAIS	WWW.SOU	RIAU.
				_	FORMAT A3		SO 8[URIAU D513I

G

Н

F

Е

D

С

