			0	₩	Þ
	ØS Contraction of the second s				
<u>ــــــــــــــــــــــــــــــــــــ</u>			LAYOUT SHOWN A	AS EXAMPLE	
CHARACTERISTICS -Standard : Based on NIL-DTL-38999 Series III -Shell Material : Composite -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles	Keying Shown as example Connector dimension Dim Nominal ØS 29.4 Max Z' 31.5 Max VV THREAD M18x1-6g		due to a use of the Products the Specifications issued by eithe (professional recommen	r any non-conformity or damage s which does not comply with er of the Parties or by a third party ndation, technical notice.) untry Jurisdiction & Control Li FR Not Listed	st
-Delivered without Souriau contacts -Temperature Range <u>:</u> -65°C to +175°C -Salt Spray : 2000 hours		ISS D Designed By:	0-2016 First Release ATE Latest modification - by Date:	CUSTOMER DR/	MOD N°
BASIC SERIES: 8D 5 - 13 J SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13	OR CONTACT TYPE : PIN		IAU WWW.SOURIAL	: 859 This documen SC it must not t communicated	t is the property of DURIAU be reproduced or without permission
PLATING : J = Olive drab Cadmium	F E	AYOUT : 13-03 FORMAT A3		AU DRG N° JO3PBL-C B	A SHEET

	т	۵	וד	т	D	0		
		Contact Layout						
4								
	Ctc A B C	3#16 13-03 X Y 2.39 1.47 0 -2.79 -2.39 1.47						
ω		-2.55						
	_							
						SOURIAU shall not be liable for a due to a use of the Products w the Specifications issued by either (professional recommend)		
N							Coun FR	
						PN	: 8D513	
					A 17-10-201 ISS DATE	6 First Release	hu	
					Designed By:	Date:	Бу	
					TITLE		Comp	
_					SCALE NA		General linear Tolerances: ±	
					SOURIAL	J WWW.So	OURIAU.	
					FORMAT	S	OURIA	

G

Н

F

Е

A3

D

С

