	ت Ω <u></u>	m		0	σ		
CHARCTERSTCS         Stradard: Based on MILDT-38899 Series II         Shell Material       : Composite         Shell Noter       : Composite         Shell Note <td:< td=""><td></td><td></td><td></td><td></td><td>IN AS EXAMPLE</td><td></td><td>4</td></td:<>					IN AS EXAMPLE		4
CHARCTERSTCS         Stradard: Based on MILDTL-38899 Series III         Shell Material       Composite         Shell Material       Shell Material         Shell Note Reserve       Shell Note Reserve	Keving	Shown as example					
BASIC SERIES:       8D       5       -       13       M       04       P       B         SHELL TYPE : Plug with RFI Shielding       Image: CONTACT TYPE : Standard Crimp Contact       Image: CONTACT TYPE : PIN(500 Matings)       SCALE       Image: CONTACT TYPE : PIN(500 Matings)       Image: CONTACT TYPE : PIN(500 Matings)       SOURIAU       SOURIAU       This document is the property of SOURIAU       SOURIAU       Image: CONTACT TYPE : PIN(500 Matings)       Image: CONTACT TYPE : PIN(500 Matings)	<ul> <li>Standard : Based on MIL-DTL-38999 Series III</li> <li>Shell Material : Composite</li> <li>Shell Plating : Nickel</li> <li>Insulator : Thermoplastic</li> <li>Contacts : Copper Alloy</li> <li>Seals &amp; Grommet : Silicon Elastomer</li> <li>Contact Plating : Gold over copper Alloy 0.8µm minimum</li> <li>Durability : 500 Mating cycles</li> <li>Delivered with Souriau contacts and Accessories</li> <li>Temperature Range : -65°C to +200°C</li> <li>Salt Spray : 2000 hours</li> </ul>	Dim         Nominal           ØS         29.4 Max           Z'         31.5 Max	ISS DATE	due to a use of the Prod the Specifications issued by e (professional recom <b>PN: 8D5</b> 5 First Release Latest modification - by	ucts which does not comply weither of the Parties or by a thir mendation, technical notice.)          Country       Jurisdiction & FR         S13M04PB	ith rd party & Control List 	
BASIC SERIES:       ab       3       1       13       W       04       P       b       Introduction of the property of sources:       to b       to b       to b       to b       859         SHELL TYPE : Plug with RFI Shielding       CONTACT TYPE : Standard Crimp Contact       ORIENTATION : B       NA       SOURIAU       WWW.SOURIAU.COM       This document is the property of source or communicated without permission         SHELL SIZE : 13       CONTACT TYPE : PIN(500 Matings)       CONTACT LAYOUT : 13-04       FORMAT       SOURIAU DRG N°       SHEET							
	SHELL TYPE : Plug with RFI Shielding       CONTACT TYPE : Standard Crimp Contact	ORIENTATION : B	- SOURIAU	Tolerar ±	AU.COM	859 This document is the property of SOURIAU it must not be reproduced or	
	PLATING : M = Nickel						

$\begin{array}{c} \textbf{Contact Layout} \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ \hline \\ & & & &$	
$\begin{array}{c} \bullet \\ \bullet $	
(Insert arrangement 13-4)	
Contact position IDX-axis (mm)Y-axis (mm)A+.000 (0.00)+.150 (3.81)B+.146 (3.71)+.035 (0.89)C+.000 (0.00)083 (2.11)D146 (3.71)+.035 (0.89)ShellArrangement no.Number of contactsSizeService rating location1344161All<	
ω	
SOURIAU shall not be l due to a use of the the Specifications issued (professional re-	Products wh by either o
	Countr FR
PN: 8	D513N
A 18-10-2016 First Release	
ISS     DATE     Latest modification - by       Designed By:     Date:	
TITLE	Compo
	eral linear lerances: ±
SOURIAU WWW.SOU	RIAU.C
	URIAU
H G F E D C	)513M

