ב ב	т (п	D	0	ω			
Z'	ØS						
	I		LAYOUT SHOV	VN AS EXAMPLE			
	Keying Shown as example						
CHARACTERISTICS	Connector dimension	7					
Standard : Based on MIL-DTL-38999 Series III	Dim Nominal ØS 29.4 Max						
-Shell Material : Composite -Shell Plating : Nickel -Insulator : Thermoplastic	Z' 31.5 Max VV THREAD M18x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
-Contacts : Copper Alloy			(professional recom				
-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum			-		& Control List Listed		
-Durability : 500 Mating cycles							
-Delivered without Souriau contacts			PN: 8D5	513M26SEL			
-Temperature Range : -65°C to +200°C		Δ 18-10-	-2016 First Release				
-Salt Spray : 2000 hours							
Mass : 18.9 g ± 10%		ISS DA Designed By:	TE Latest modification - by Date:	CUS	TOMER DRAWING	MOD N°	
		TITLE	TITLE Composite Plug 8D series				
BASIC SERIES: 8D 5 - 13 M	26 S E L	SCALE	General		PRDS / PROJECT		
SHELL TYPE : Plug with RFI Shielding	Delivered	W/O Contacts NA	Toleral ±		859		
CONTACT TYPE : Standard Crimp Contact	OP				This document is the propert SOURIAU		
SHELL SIZE : 13	CONTACT TYPE : SOCKET		AU WWW.SOURI		it must not be reproduced o communicated without permis		
PLATING : M = Nickel		AYOUT : 13-26	SOUF	RIAU DRG N°		SHEET	
		A3		I3M26SEL-C		1/2	

-	Ŧ	G	г П	m	D	0
		Contact Layout				
4		26				
	[2#12 6#22D 13-26	1			
c.	Ctc A B C D E F 1 2	X Y 0 3.47 2.47 4.34 2.47 -4.34 0 -3.47 -2.47 -4.34 -2.47 -4.34 3.25 0 -3.25 0				
	-					SOURIAU shall not be liable for an due to a use of the Products wh the Specifications issued by either or (professional recommendat
N						Countr FR
					A 18-10-20 ISS DATE Designed By:	PN: 8D513N 16 First Release Latest modification - by Date:
					SCALE	Compo General linear
_					NA	Tolerances:
					FORMAT A3	J WWW.SOURIAU.C SOURIAU 8D513M2
L	Н	G	F	E	D	С

