	I G	П	m			0	C	α	A		
	< <u>Z'</u>										
4		ØS									4
ω						LAYC	OUT SHOWN AS EXAMPL	E			3
	Keying Shown as example										
	CHARACTERISTICS	F	Connector dimension]							
	Standard : Based on MIL-DTL-38999 Series III -Shell Material : Composite		DimNominalØS35.7 MaxZI24.5 Max				et ha liabla far any non-c	onformity or dama	~~~		
	Shell Plating : Nickel Shell Plating : Nickel Insulator : Thermoplastic Contacts : Copper Alloy				SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)						
	-Seals & Grommet : Silicon Elastomer						Country	Jurisdiction & Co			
N	 -Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles 						FR	Not Liste	ed		2
	-Delivered with Souriau contacts and Accessories		PN: 8D517M06HB A 17-10-2016 First Release								
	-Temperature Range : -65°C to +200°C -Salt Spray : 2000 hours										
					ISS DATE	Latest modification	ו - by			MOD N°	-
					Designed By:	Date:			IER DRAWING		-
							TITLE Composite Plug 8D series				
	BASIC SERIES: 8D 5 - 17 N	1 06 Н В			SCALE .		General linear Tolerances:	NPRD	S / PROJECT 859		
<u> </u>	SHELL TYPE : Plug with RFI Shielding				NA		±	This	document is the prope	erty of	1
	ONTACT TYPE : Standard Crimp Contact ORIENTATION : B IELL SIZE : 17 CONTACT TYPE : PIN (1500 Matings)				SOURIAU			SOURIAU it must not be reproduced or nmunicated without permission			
	PLATING : M = Nickel		CONTACT TIPE . FIN (13		FORMAT		SOURIAU DRO			SHEET	
		1			A3		8D517M06H			1/2	
	H G	F	I E		D	С	E	3	А		

Г	T	۵	Т	т		0	ω	A		
	Contact Lay	put								
4	E At									4
		∋ ^B) +x								
	C⊕ €Y									
	(mm) A +.121 (3.07) B +.241 (6.12)	n Y-axis (mm)								
ω	D 241 (6.12) - E 121 (3.07) - F +.000 (0.00) -	000 (0.00) 209 (5.31) .000 (0.00)								3
	Shell sizeArrangement no.Number of contactsSize contacts17-6612	Service rating Contact location Supersedes I All MS20053-6								
						SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
N						CountryJurisdiction & ContrFRNot Listed				2
						PN: 8D517M06HB				
					ISS DATE Designed By:	Latest modification - by Date:	CUS	TOMER DRAWING	MOD N°	
					TITLE	TITLE Composite Plug 8D series				
→					SCALE	-{	al linear N rances: ±	PRDS / PROJECT 859		1
						SOURIAU This document is the proper SOURIAU SOURIAU it must not be reproduced				
					FORMAT		RIAU DRG N°	ommunicated without per	rmission SHEET	-
				1	A3		517M06HB-C		2/2	
L	Н	G	F	E	D	С	В	A		J