ב בר	П	ш	D		0	ω	>		7
A	ØS								4
ω					LAYOUT SH	OWN AS EXAMPLE			3
	Keying Shown as e	example							
CHARACTERISTICS		Connector dimension							
-Standard : Based on MIL-DTL-38999 Series III		DimNominalØS35.7 Max							
-Shell Material : Composite -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy		Z' 31.5 Max VV THREAD M25x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)					
-Seals & Grommet : Silicon Elastomer						Country Jurise FR	diction & Control List Not Listed		2
 Contact Plating : Gold over copper Alloy 0.8μm minimum Durability : 500 Mating cycles Delivered with Souriau contacts and Accessories 					PN: 8[D517M26AD	NotEstea		
-Temperature Range : -65°C to +200°C				17-10-2016 Fi	rst Release				_
-Salt Spray : 2000 hours									
			ISS Designed		Latest modification - by Date:		CUSTOMER DRAWING	MOD N°	+
				ITLE	Composite Plug 8D series				
→ BASIC SERIES: 8D 5 - 17 M SHELL TYPE : Plug with RFI Shielding	A 26 A D		SCALE			eral linear erances: ±	NPRDS / PROJECT 859		_
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17		ORIENTATI CONTACT TYPE : PIN(500 Ma	SUU	JRIAU	WWW.SOU	RIAU.COM	This document is the pr SOURIAU it must not be reprod	uced or	
				<u>т</u>			communicated without	SHEET	_
PLATING : M = Nickel		CONTACT LAYOUT :	. 17-20			JRIAU DRG N°			
			A3		0	517M26AD-C		1/2	

