	т п		0		Þ
	Keying Shown as example		LAYOUT SHOWN	AS EXAMPLE	
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal	]			
-Shell Material : Composite -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum	ØS         35.7 Max           Z'         31.5 Max           VV THREAD         M25x1-6g		SOURIAU shall not be liable for any non-conformity or damage         due to a use of the Products which does not comply with         the Specifications issued by either of the Parties or by a third party         (professional recommendation, technical notice.)         Country       Jurisdiction & Control List         FR       Not Listed		
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D517M26BC		
-Temperature Range65°C to +200°C					
-Salt Spray : 2000 hours			A     17-10-2016     First Release       ISS     DATE     Latest modification - by     MC		
Mass : 36.3 g ± 10%		ISS DA Designed By:	TE Latest modification - by Date:	CUSTOMER DRA	MOD N°
		TITLE	Со	Composite Plug 8D series	
BASIC SERIES: 8D 5 - 17 M	26 B C	SCALE	General lir Tolerance ±	es: 859	
SHELL TYPE : Plug with RFI Shielding			SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission		
SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact			AU WWW.SOURIA	U.COIVI it must not be	e reproduced or
SHELL TYPE : Plug with RFI Shielding	ORIEI CONTACT TYPE : SOCKET(5) CONTACT LAY	00 Matings)		U.COIVI it must not be	e reproduced or

