ſ	т <u>о</u> т т		0	□ >	
4	Z Market Market				4
ω	Keying Shown as example		LAYOUT SHOWN AS EXAMPL	LE	3
	CHARACTERISTICS Connector dimension -Standard : Based on MIL-DTL-38999 Series III Dim Nominal				
N	-Shell Material : Aluminium ØS 35.7 Max -Shell Plating : Olive drab Cadmium Z 31 Max -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum		SOURIAU shall not be liable for any non- due to a use of the Products which do the Specifications issued by either of the P (professional recommendation, te Country FR	es not comply with arties or by a third party	2
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories				
	-Temperature Range _: -65°C to +175°C -Salt Spray : 500 hours	A 17-10-2016 First Release			
		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	N°
		TITLE Aluminium Plug 8D series			
_	BASIC SERIES: 8D 5 - 17 W 22 P A SHELL TYPE : Plug with RFI Shielding	SCALE	General linear Tolerances:	NPRDS / PROJECT 859	
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17 CONTACT TYPE : PIN(500 Matings)		SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission communicated without permission		
	PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 17-22	FORMAT	SOURIAU DR	G N° SHEET	
		A3	8D517W22F	PA-C 1/2	

	Ŧ	۵	н г	m		0	
4		Contact Layout 22					
ω	Ctc A B C D	2#12 2#8 Triax 17-22 X Y 0 4.57 6.32 0 0 -4.57 -6.32 0					
						SOURIAU shall not be liable due to a use of the Produ the Specifications issued by ei (professional recomn	ucts w ither c
N						PN: 8D5	Count FR
_					A 17-10-20 ISS DATE Designed By: TITLE	Date:	umiı
_					SCALE NA SOURIA	General li Tolerand ±	linear ices:
	Н	G	F	E	FORMAT A3 D	SOUR 8D51	IAL

