ت ت ا	т (П	D	0	₩ >		
	the second		LAYOUT SHOWN AS EXAMP	LE		
CHARACTERISTICS	Keying Shown as example					
-Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal					
-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
-Contact Plating : Gold over copper Alloy 0.8µm minimum			FR Not Listed			
-Durability : 500 Mating cycles -Delivered without Souriau contacts			PN: 8D517W22PBL			
-Temperature Range <u>-</u> -65°C to +175°C -Salt Spray : 500 hours		A 17-10-2016	First Release			
-Salt Spray : 500 hours		ISS DATE	Latest modification - by	MOD N		
		Designed By:	Date:	CUSTOMER DRAWING		
		TITLE	TITLE Aluminium Plug 8D series			
BASIC SERIES: 8D 5 - 17 W 22		SCALE -	General linear Tolerances:	NPRDS / PROJECT 859		
SHELL TYPE : Plug with RFI Shielding	Delivered W/O Cont			This document is the property of		
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17	ORIENTATIO	- SUURIAU	WWW.SOURIAU.COM			
	CONTACT TIPE : PIN(300 Math		FORMAT SOURIAU DRG N° SHEET			
DIATING : W = Olive dreb Cadmium		1-22	SUUKIAU DE			
PLATING : W = Olive drab Cadmium		— A3	8D517W22F			

		۵	п –	m	D	0
4		Contact Layout 22				
	Ctc A B C	2#12 2#8 Triax 17-22 X Y 0 4.57 6.32 0 0 -4.57				
3		-6.32 0				SOURIAU shall not be liable for ar
2						due to a use of the Products w the Specifications issued by either of (professional recommenda Count FR PN: 8D517V
					A 17-10-20 ISS DATE Designed By: TITLE	16 First Release
1						SOURIAU
	Н	G	F	E	A3 D	8D517W

