ک ا	т п	D	0	œ			
			LAYOUT SI	HOWN AS EXAMPLE			
	Keying Shown as example						
CHARACTERISTICS	Connector dimension	7					
-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal ØS 35.7 Max	-					
-Shell Material : Composite -Shell Plating : Without Plating	Z 31 Max			iable for any non-conformity or Products which does not comply			
-Insulator : Thermoplastic	VV THREAD M25x1-6g		the Specifications issued	by either of the Parties or by a t	hird party		
-Contacts : Copper Alloy				commendation, technical notice			
-Seals & Grommet : Silicon Elastomer							
-Contact Plating : Gold over copper Alloy 0.8μm minimum					n & Control List t Listed		
-Durability : 500 Mating cycles							
-Delivered without Souriau contacts			PN: 8D517X75PCL				
-Temperature Range <u>-</u> -65°C to +175°C							
-Salt Spray : 2000 hours		A 1	8-10-2016 First Release				
Mass : 22.3 g ± 10%		ISS	DATE Latest modification - by		MOD) N°	
		Designed	By: Date:	CU	STOMER DRAWING		
		т	E Composite Plug 8D series				
BASIC SERIES: 8D 5 - 17 X 75	5 P C L	SCALE	Gen	eral linear	NPRDS / PROJECT		
				lerances:	859		
SHELL TYPE : Plug with RFI Shielding		N/O Contacts NA		±	This document is the property of		
CONTACT TYPE : Standard Crimp Contact			IRIAU WWW.SOU		SOURIAU it must not be reproduced or		
SHELL SIZE : 17	CONTACT TYPE : PIN				communicated without permission		
PLATING : X = Without Plating	CONTACT LA	YOUT : 17-75	30	URIAU DRG N°	SHE	ET	
		A3	80	0517X75PCL-C	1/2	2	
					1		

-	Ŧ	Q	нт —	т		0
4		Contact Layout 75				
	Ctc A B	2#8 Triax 17-75 X Y 0 4.75 0 -4.75				
ယ						
						SOURIAU shall not be liable for an due to a use of the Products wh the Specifications issued by either of (professional recommendat
N					A 18-10-20	Countr FR PN: 8D517X
					ISS DATE Designed By: TITLE	Date:
_					SCALE NA SOURIA	General linear Tolerances: ± U WWW.SOURIAU.C SOURIAU
	Н	G	F	E	A3	8D517X7

