ב ₪ 	т п		0	σ			
A Linead						4	
			LAYOUT SHOT	WN AS EXAMPLE		3	
	Keying Shown as example						
CHARACTERISTICS	Connector dimension						
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum	DimNominalØS35.7 MaxZ31 MaxVV THREADM25x1-6g		due to a use of the Pro the Specifications issued by		with hird party	2	
 Contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories 			PN: 8D	517Z22AN			
-Temperature Range _: -65°C to +175°C -Salt Spray : 500 hours		A 18	-10-2016 First Release				
			ISS DATE Latest modification - by MO Designed By: Date: CUSTOMER DRAWING		MOD N STOMER DRAWING	<u>√°</u>	
		тп	TITLE Aluminium Plug 8D series				
→ BASIC SERIES: 8D 5 - 17 Z 22 → SHELL TYPE : Plug with RFI Shielding	AN	SCALE	Genera Tolera ±	nces:	NPRDS / PROJECT 859		
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17				SOURIAU This document is the property of SOURIAU it must not be reproduced or communicated without permission			
PLATING : Z = Black Zinc Nickel	L CONTACT LA			RIAU DRG N° 17Z22AN-C	SHEET 1/2		
H G	FE	D		B	A 1/2		

	工	۵	г П	m		0	
4		Contact Layout 22					
	Cto	2#12 2#8 Triax 17-22 X Y					
۵	Ctc A B C D	X Y 0 4.57 6.32 0 0 -4.57 -6.32 0					
	+					SOURIAU shall not be liable for due to a use of the Products	s w
0						the Specifications issued by eithe (professional recommen Cou	nda
					A 18-10-20	PN: 8D51	7
					ISS DATE Designed By: TITLE	Latest modification - by Date: Alum	niı
_					SCALE NA SOURIA	General linea Tolerances: ±	:
					FORMAT A3	SOURIA 8D517	٩٢
	Н	G	F	E	D	C	_

