	т п		0	₿ ▶	
ØS~					
			LAYOUT SHOWN AS EXAI	MPLE	
	Keying Shown as example				
CHARACTERISTICS	Connector dimension Dim Nominal	1			
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium	ØS 35.7 Max	1	SOURIAU shall not be liable for any n	on-conformity or damage	
-Shell Plating : Black Zinc Nickel	Z 31 Max VV THREAD M25x1-6g	]	due to a use of the Products which	does not comply with	
-Insulator : Thermoplastic			the Specifications issued by either of th (professional recommendation		
-Contacts : Copper Alloy				·	
-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum			Country FR	Jurisdiction & Control List Not Listed	-
-Durability : 500 Mating cycles					
-Delivered without Souriau contacts			PN: 8D517Z2	2PDL	
-Temperature Range : -65°C to +175°C		A 18-10-2016	First Polosso		
-Salt Spray : 500 hours					
		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°
		TITLE	TITLE Aluminium Plug 8D series		
		SCALE	General linear		
BASIC SERIES: 8D 5 - 17 Z	22 P D L		Tolerances:	NPRDS / PROJECT <b>859</b>	
SHELL TYPE : Plug with RFI Shielding	Delivered W			This document is the pro	operty of
CONTACT TYPE : Standard Crimp Contact		SOURIAU	WWW.SOURIAU.CO	COLIDIALI	
SHELL SIZE : 17	CONTACT TYPE : PIN(5			communicated without p	ermission
	CONTACT LAY	OUT : 17-22 FORMAT	SOURIAU D	DRG N°	SHEET
PLATING : Z = Black Zinc Nickel		A3	8D517Z22		1/2

	т	۵	н п	m		0	
4		Contact Layout 22					
	Ctc A B C D	2#12 2#8 Triax 17-22 X Y 0 4.57 6.32 0 0 -4.57 -6.32 0					
						SOURIAU shall not be liable fo due to a use of the Product the Specifications issued by eith	ts w ner o
27						(professional recomme	ount FR
_					A 18-10-20 ISS DATE Designed By: TITLE	16 First Release Latest modification - by Date: Alur	miı
					SCALE NA SOURIA	General line Tolerances ±	s:
	Н	G	F	E	FORMAT A3 D	SOURIA 8D517	

