⊥	Q	П	m			0	Φ		
	A Thread	S Contraction of the second se							2
						LAYOUT SHOWN A	AS EXAMPLE		3
		Kouing Chour							
CHARACTERISTICS		Keying Shown							
-Standard : Based on MIL-DTL-38	3999 Series III	F	Connector dir Dim	nension Nominal					
-Shell Plating : Black 2 -Insulator : Therm -Contacts : Coppe -Seals & Grommet : Silicon	-Shell Material : Aluminium ØS 35.7 Max -Shell Plating : Black Zinc Nickel Z 31 Max -Insulator : Thermoplastic VV THREAD M25x1-6g -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer					SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed			
-	lating cycles					PN: 8D51	1		2
	to +175°C				A 18-10-2016	First Release			
-Salt Spray : 500 ho	iurs				ISS DATE	Latest modification - by		M	OD N°
					Designed By:	Date:	CU	STOMER DRAWING	
					TITLE Aluminium Plug 8D series				
BASIC SERIES:	8D 5 - 17 Z	22 P E	L	Delivered W/O Contacts	SCALE	General line Tolerances		NPRDS / PROJECT 859	
CONTACT TYPE : Standard Cri SHELL SIZE : 17	np Contact		CONTA	ORIENTATION : E CT TYPE : PIN(500 Matings)	SOURIAU	WWW.SOURIAL		This document is the property of SOURIAU it must not be reproduced or	
PLATING : Z = Black Zind	Nickel		CONTA	CONTACT LAYOUT : 17-22	FORMAT		AU DRG N°	communicated without permissio	HEET
FLATING . Z = DIACK ZITT				CONTACT LATUUT . 17-22	A3		Z22PEL-C		1/2
				1		XII517	//////		エ/ム I

	т	۵	г	m	D	0
4		Contact Layout 22				
	Ctc A B C	2#12 2#8 Triax 17-22 X Y 0 4.57 6.32 0 0 -4.57				
	D	-6.32 0				SOURIAU shall not be liable for due to a use of the Products the Specifications issued by eithe
N						(professional recommen
					A 18-10-20 ISS DATE Designed By: TITLE	016 First Release Latest modification - by Date: Alum
					SCALE NA SOURIA	General linea Tolerances: ± U WWW.SOURIAU SOURIA
	Н	G	F	E	A3	8D517

