ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב	т (П		0	Φ	A	
A						4
	Keying Shown as example		LAYOUT SHOWN	N AS EXAMPLE		3
CHARACTERISTICS	Connector dimension Dim Nominal					
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles -Delivered with Souria⊔ contacts and Accessories	ØS35.7 MaxZ31 MaxVV THREADM25x1-6g		the Specifications issued by eit (professional recomm	icts which does not comply w ther of the Parties or by a thin nendation, technical notice.)	ith rd party & Control List	2
-Temperature Range <u>-</u> -65°C to +175°C		A 18-10-2016	First Release			
-Salt Spray : 500 hours 		ISS DATE Designed By:	Latest modification - by Date:	CUST	MOD N TOMER DRAWING	<u>√°</u>
		TITLE	TITLE Aluminium Plug 8D series			
BASIC SERIES: 8D 5 - 17 Z 75 SHELL TYPE : Plug with RFI Shielding - 17 Z 75 CONTACT TYPE : Standard Crimp Contact - 17 Z 75	S N ORIENTATIO	SCALE NA	General lin Toleranc ±	xes:	PRDS / PROJECT 859 This document is the property of	1
SHELL SIZE : 17	CONTACT TYPE : SOCKET(500 Mat	Matings) SOURIAU WWW.SOURIAU.COIM it must not be reproduced or communicated without permission				
PLATING : Z = Black Zinc Nickel	CONTACT LAYOUT : 1	I7-75 FORMAT A3		IAU DRG N° L7Z75SN-C	SHEET 1/2	
H G	F	D	C	В	А	

-	Ŧ	Q	нт — — — — — — — — — — — — — — — — — — —	m		0
4		Contact Layout 75				
	Ctc A B	2#8 Triax 17-75 X Y 0 4.75 0 -4.75				
ယ						
	_					SOURIAU shall not be liable for an due to a use of the Products wh the Specifications issued by either or (professional recommendat
N					A 18-10-20	Countr FR PN: 8D5172
					ISS DATE Designed By: TITLE	Date:
					SCALE NA SOURIA	SOURIAU
	Н	G	F	E	A3 D	8D517Z

